
SINGLE DISHDRAWER™ DIMENSIONS

DD24SDFX7, DD24SI7, DD24SCX7, DD24SCB7, DD24SCW7



DIMENSIONS INCHES (MM)	DD24SDFX7		DD24SI7		DD24SCX7		DD24SCW7, DD24SCB7	
	Designer		Intergrated		Classic		Black Classic, White Classic	
A overall height[1] of product (incl. front panel height)	16 ⅛"	(410)	16 ⅛"	(410)	16 ⅛"	(410)	16 ⅛"	(410)
B overall width of product	23 9⁄16"	(599)	23 9⁄16"	(599)	23 9⁄16"	(599)	23 9⁄16"	(599)
C overall depth of product (excl. handle)	22 ½"	(571)	22 ½ "	(571)[3]	22 15⁄16"	(582)	22 15⁄16"	(582)
D depth of chassis (to back of front panel)	21 ¾"	(553)	21 ¾"	(553)	21 ¾"	(553)	21 ¾"	(553)
E maximum extension of drawer (excl. handle)	21 7⁄16"	(545)	21 7⁄16"	(545)[3]	21 ⅞"	(556)	21 ⅞"	(556)
F depth of front panel (excl. handle)	1 1⁄16"	(18)	⅝ - 1 3⁄16"	(16-20)	1 ⅛"	(29)	1 ⅛"	(29)
G height[1] of chassis	16 ⅛"	(410)	16 ⅛"	(410)	16 ⅛"	(410)	16 ⅛"	(410)
H depth of handle	1 ⅝"	(41)	n/a	n/a	n/a	n/a	n/a	n/a
I height of front panel	15 1 1⁄16"	(398)	16 1⁄16"	(408)[4]	15 ½"	(394)	15 ½"	(394)
J height of ventilation gap below front panel	5⁄16"	(8)	min. 1⁄16"	(2)	¼"	(7)	¼"	(7)
K height from top of handle to top of front panel	2 ½"	(64)	n/a	n/a	n/a	n/a	n/a	n/a


[1]includes 1⁄16" (2 mm) high bracket slots [2]Includes cavity bracket [3]Assuming front panel thickness of 1 1⁄16" (18 mm)


[4]Recommended for a 1⁄16" (2 mm) ventilation gap below panel, if cavity height is 16 ¼" (412 mm) [5]Recommended for a 1⁄16" (2 mm) ventilation gap below panel

Product dimensions and specifications are listed as a guide only. For complete installation instructions and specifications, refer to the product Use & Care Guide/Installation Instructions available at www.fisherpaykel.com


SINGLE DISHDRAWER™ CABINETRY DIMENSIONS

DD24SDFX7, DD24SI7, DD24SCX7, DD24SCB7, DD24SCW7





Minimum clearances from adjacent cabinetry



DIMENSIONS INCHES (MM)	DD24SDFX7		DD24DI7, DD24SHI7		DD24SCX7, DD24SCHX7		DD24SCB7, DD24SCW7	
	Designer		**Integrated**		**Classic**		**Black Classic, White Classic**	
L inside height of cavity	min. 16 ¼"	(412)	min. 16 ¼"	(412)	min. 16 ¼"	(412)	min. 16 ¼"	(412)
M inside width of cavity	23 ⅝"	(600)	23 ⅝"	(600)	23 ⅝"	(600)	23 ⅝"	(600)
N inside depth of cavity	min. 22 1/16"	(560)	min. 22 1/16"	(560)	min. 22 1/16"	(560)	min. 22 1/16"	(560)

Product dimensions and specifications are listed as a guide only. For complete installation instructions and specifications, refer to the product Use & Care Guide/Installation Instructions available at www.fisherpaykel.com