QUICK REFERENCE GUIDE > RGV3-485GD-N

Gas Range, 48", 5 Burners with Griddle

Series 7 | Professional

Stainless Steel | Natural gas



With Professional styling, this large range has five burners delivering powerful high heat, a griddle and two gas ovens.

- Griddle with burners that deliver up to 23,500 BTU heat per burner, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4
Width	47 7/8
Depth	29 1/8

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey. The griddle plate allows you to cook several foods at once.

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

23500 BTU
18500BTU
18500BTU
23500BTU
18500BTU
18500BTU
24000BTU
121500 BTU
5
5
5.3cu ft
2.4cu ft
3.9cu ft
•
3 wire
•
½ NPT, min. %" 🛚 flex line
6" to 9" W.C

QUICK REFERENCE GUIDE > RGV3-485GD-N

Oven	fea	tu	ires

Auto re-ignition system	•
Electronic oven control	•
Full extension telescopic	•
Infrared Broiler	•
Internal light	•
Titanium coated, illuminated	•

Oven functions

n .

Bake		•
Broil		•
Convection ba	ke	
Slow cook		

Oven performance

Main oven - Bake power	28,000 BTU
Main oven - Broil power	18,500 BTU
Secondary oven - Bake power	18,000 BTU

Power requirements

Amperage	15A
Supply frequency	60Hz

Product dimensions

Depth	29 1/8"
Height	35 3/4 - 36 3/4'
Width	47 7/8"

Rangetop features

Sealed range top

Vent trim included	•

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48""

Safety

ADA compliant	•
Full extension telescopic	

Secondary oven features

3/4 Extension racks	
Electronic oven control	
Internal light	

Secondary oven functions

Bake	•
Convection bake	•
Number of secondary oven	4
Proof	•
Slow cook	•

SKU	81996

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > RGV3-485GD-N Date: 02.05.2024 > 3

Other product downloads available at fisherpaykel.com



Guide d'utilisation FR



User Guide



Service & Warranty



Guide d'installation FR



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com