

FISHER & PAYKEL

PRELIMINARY SPECIFICATION GUIDE

INTEGRATED COLUMN REFRIGERATOR FREEZER, 30"



OVERVIEW

Mix and match these Integrated Column Refrigerators or Freezers for true design freedom. Designed to fit flush with cabinetry with minimal 1/8" gaps, the Integrated Columns can be installed separately or paired. These are available in a range of sizes and can be fitted with stainless steel or custom door panels.

MODELS

Integrated Column Refrigerator Freezer, 30", Panel Ready, Ice & Water, Bottom Freezer, Right Hinge, Stainless Steel Interior RS3084WRUK1

Integrated Column Refrigerator Freezer, 30", Panel Ready, Ice & Water, Bottom Freezer, Left Hinge, Stainless Steel Interior RS3084WLUK1

Integrated Column Refrigerator Freezer, 30", Panel Ready, Ice & Water, Bottom Freezer, Right Hinge RS3084WRU1

Integrated Column Refrigerator Freezer, 30", Panel Ready, Ice & Water, Bottom Freezer, Left Hinge RS3084WLU1

FEATURES

- ① Flush fit design with 1/8" gaps
- ② Bright LED interior lighting
- ③ Two independent variable temperature zones
- ④ Refrigerators and freezers each have three food modes
- ⑤ 84" height
- ⑥ Cantilevered glass shelves
- ⑦ Easy to access and use touch-control panel
- ⑧ Hidden ventilation grille
- ⑨ Energy efficient
- ⑩ ActiveSmart™ helps keep food fresher for longer

ACCESSORIES

- ① Four handle styles
- ② Easy-to-install joiner kit for paired installation (incl. with all freezer models)
- ③ Stainless steel door panels
- ④ Stainless steel toe kick

FISHER & PAYKEL


PRELIMINARY SPECIFICATION GUIDE

INTEGRATED COLUMN REFRIGERATOR FREEZER, 30"


SPECIFICATIONS

Dimensions	H 84" (2134mm) x W 29 3/4" (610mm) x D 24" (610mm)
Door Clearance	32" (813mm)
Drawer Clearance*	15 3/4" (400mm)
Weight	309lb (140kg)
Door Hinge	Hettich KO5
Electrical	
Supply	115VAC, 60Hz
Service	10-amp circuit
Receptacle	3-prong grounding-type
Plumbing	
Supply	1/4" (6mm) comp. stainless steel braided hose
Pressure	Min 150kPa (22psi), max 827kPa (120psi) @ 68°F (20°C)

*Excl. handle depth.




PRODUCT DIMENSIONS



		in	mm
(A)	Overall height	84	2134
(B)	Overall width	29 3/4	756
(C)	Overall depth (excl. front door panel)	24	610
(D)	Height from bottom of product to top of drawer panel	34 3/8	873
(E)	Depth of toe kick (excl. front of door panel)	2 7/8 - 4	73 - 102
(F)	Height of toe kick*	2 - 6	51 - 152
(G)	Depth of door (widest opening) measured from front of door	32	813
(H)	Height of refrigerator door panel	49 3/8	1254
(I)	Height of freezer drawer door panel	30 3/8	772
(J)	Width of front panels	29 3/4	756
(K)	Depth of front panels (excl. handles)	3/4	19

*Standard toe kick height is 4" (102mm) with the optional stainless door panel. For custom door panel installation, a custom toe kick of 2-6" (51-152mm) can be manufactured and fitted by cabinetmaker. The custom door panel height needs to be adjusted accordingly.

CAVITY DIMENSIONS: STANDARD INSTALLATION



		in	mm
(A)	Overall height of cavity	84	2134
(B)	Overall width of cavity	30	762
(C)	Minimum overall depth of cavity*	25	635
	Minimum cabinetry gap clearance from edge of door panels	1/8	3
	Minimum required finished return, sides and top of cavity	4	102
	Minimum door clearance to adjacent wall (90° - full internal access)	4 1/3	110
	Minimum door clearance to adjacent wall (115° - full door opening)	16 1/2	419

*Assumes a door panel thickness of 3/4".