



DD24SV2T9\_N

24" Single DishDrawer™  
Dishwasher, 7 Place  
Settings, Sanitize (Tall)

Professional

This Fisher & Paykel Single DishDrawer™ Dishwasher makes life easier with minimal bending when loading and the ability to wash small loads quickly.

Stainless Steel



A PEACE OF MIND SALE  
24 Hours 7 Days a Week Customer Support  
T 1.888.936.7872 W

Dimensions

|        |           |
|--------|-----------|
| Depth  | 22 3/4"   |
| Height | 17 7/8"   |
| Width  | 23 13/16" |

Features & Benefits

**Ease of use**  
DishDrawer™ Dishwashers are as easy to open and close as kitchen drawers and can be conveniently positioned at bench height for ease of loading and minimal bending. Flexible racking allows you to make adjustments to fit in a variety of dishes.

**Designed to match**  
DishDrawer™ Dishwashers can be installed in any kitchen space and are designed to match the Fisher & Paykel family of kitchen appliances, with matching handles, premium styling and quality materials.

**Quick, Sanitize and Extra Dry options**  
The Quick wash modifier delivers a faster wash while maintaining performance. The Sanitize option provides extra protection killing 99.9% of bacteria in the final rinse. The Extra Dry setting is perfect for plastic dishes.

**Quiet performer**  
Running at a very low decibel rate, these DishDrawer™ Dishwashers do their job without making a fuss. The combination of intelligent technology and simple mechanics means greater reliability and excellent wash performance.

Specifications

|                      |           |
|----------------------|-----------|
| <b>Accessories</b>   |           |
| Cutlery basket       | 1         |
| Knife clip           | •         |
| Square handle option | AHV2-DD24 |

|                                      |        |
|--------------------------------------|--------|
| <b>Capacity and loading</b>          |        |
| Accommodates plates up to            | 12.25" |
| Adjustable height, foldable cupracks | •      |
| Fold down tines                      | •      |
| Pitch adjustable tines               | •      |
| Place settings                       | 7      |

|  |   |
|--|---|
| <b>Controls</b>                                    |   |
| Child safety lock                                  | • |
| Electronic fault/Diagnostic indicator              | • |
| End of cycle beeps                                 | • |
| Energy saving delay start option of up to 12 hours | • |
| Internal wash selector                             | • |
| Rinse aid indicator light and lens                 | • |

|                                  |   |
|----------------------------------|---|
| <b>Features</b>                  |   |
| Fan assisted drying              | • |
| Flow through detergent dispenser | • |
| Quiet operation                  | • |
| SmartDrive™ technology           | • |

|                     |   |
|---------------------|---|
| <b>Measurements</b> |   |
| ADA compliant       | • |

|  |                        |                                |                                |   |
|--|------------------------|--------------------------------|--------------------------------|---|
| Performance                            |                        | Wash Programmes                |                                | The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2019 |
| Energy star                            | •                      | Delicate                       | •                              |   |
| Energy usage                           | 144 kWh/year           | Delicate eco                   | •                              |   |
| Noise (dBA) on gentle cycle top drawer | 44 dBA                 | Eco options                    | •                              | Other product downloads available at <a href="http://fisherpaykel.com">fisherpaykel.com</a>   |
| Water usage                            | 1.64 gal/cycle         | Extra Dry                      | •                              |   |
| Power requirements                     |                        | Fast                           | •                              |   |
| AMP draw                               | 5 A                    | Fast Eco                       | •                              |   |
| Rated current                          | 15 A                   | Heavy                          | •                              |   |
| Supply frequency                       | 60 Hz                  | Heavy eco                      | •                              |   |
| Supply voltage                         | 120 V                  | Medium                         | •                              |   |
| Wire                                   | 3                      | Normal eco                     | •                              |   |
| Style And Series                       |                        | Quick                          | •                              |   |
| Product Style                          | Professional           | Rinse                          | •                              |   |
| Warranty                               |                        | Sanitise                       | •                              |   |
| Warranty                               | Limited 2 Year Parts & | Wash modifiers                 | 3                              |   |
|  | Labor                  | Wash programs                  | 15                             |   |
|  |                        | Water connection               |                                |   |
|  |                        | Supplied hose to suit 9mm male | •                              |   |
|  |                        | compression fitting            |                                |   |
|  |                        | Water connection               | Max 140°F                      |   |
|  |                        | Water pressure                 | 0.03 Mpa - 1 Mpa (4.3-145 psi) |   |
|  |                        | SKU                            | 71402                          |   |