


DATA SHEET



24" DOUBLE DISHDRAWER™

Model no:

DD24DAB9

(refer page 2 for metric measurements)

Dimensions	in
Ⓐ Overall height* of DishDrawer™	32 5/16" - 34 5/8"
Ⓑ Overall width of DishDrawer™	23 9/16"
Ⓒ Overall depth of DishDrawer™	22 9/16"
Ⓓ Depth of chassis	21 3/4"
Ⓔ Depth of front panel	13/16"
Ⓕ Height of chassis	31 15/16"
Ⓖ Height of drawer fronts	29 3/4"
Ⓗ Height of upper front panel	15 1/2"
Ⓘ Height of lower front panel	14"
Ⓢ Height from floor to bottom of lower front panel	2 3/16" - 4 9/16"
Ⓣ Height from top of front panel to top of chassis	5/16"
Ⓤ Ventilation gaps between panels	1/4"
Ⓦ Height of toekick panel	2 13/16" - 5"
Ⓧ Depth of toekick recess	1 1/2" - 4"
Ⓨ Height of adjustable levelling feet	3/8" - 2 11/16"
Ⓩ Maximum extension of drawer from front datum	21 9/16"

* includes mounted feet

Minimum Clearances	in
Height of cavity	min 32 5/16"
Width of cavity	23 5/8"
Depth of cavity	min 22 1/16"
Minimum clearance from a corner cupboard	1/2"

Note: Service outlet at rear extends both sides, hoses and cords can be routed to either or both.


INDICATES CABINETRY / PRODUCT DATUM -----
INDICATES CABINETRY CLEARANCES -----

DATE: 07.09.2016

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit www.fisherpaykel.com

Fisher & Paykel

DATA SHEET



24" DOUBLE DISHDRAWER™

Model no:

DD24DAB9

(refer page 1 for imperial measurements)

Dimensions	mm
(A) Overall height* of DishDrawer™	820 - 880
(B) Overall width of DishDrawer™	599
(C) Overall depth of DishDrawer™	573
(D) Depth of chassis	553
(E) Depth of front panel	20
(F) Height of chassis	811
(G) Height of drawer fronts	756
(H) Height of upper front panel	393
(I) Height of lower front panel	356
(J) Height from floor to bottom of lower front panel	56-116
(K) Height from top of front panel to top of chassis	8
(L) Ventilation gaps between panels	7
(M) Height of toekick panel	72 - 127
(N) Depth of toekick recess	38 - 102
(O) Height of adjustable levelling feet	9 - 69
(P) Maximum extension of drawer from front datum	547

* includes mounted feet

Minimum Clearances	mm
Height of cavity	min 820
Width of cavity	600
Depth of cavity	min 560
Minimum clearance from a corner cupboard	13

Note: Service outlet at rear extends both sides, hoses and cords can be routed to either or both.

INDICATES CABINETRY / PRODUCT DATUM -----

INDICATES CABINETRY CLEARANCES -----

DATE: 07.09.2016

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit www.fisherpaykel.com

Fisher & Paykel