


DATA SHEET



24" DOUBLE DISHDRAWER™

Model no:

DD24DAW9

(refer page 2 for metric measurements)

Dimensions	in
Ⓐ Overall height* of DishDrawer™	32 5/16" - 34 5/8"
Ⓑ Overall width of DishDrawer™	23 9/16"
Ⓒ Overall depth of DishDrawer™	22 9/16"
Ⓓ Depth of chassis	21 3/4"
Ⓔ Depth of front panel	13/16"
Ⓕ Height of chassis	31 15/16"
Ⓖ Height of drawer fronts	29 3/4"
Ⓗ Height of upper front panel	15 1/2"
Ⓘ Height of lower front panel	14"
Ⓢ Height from floor to bottom of lower front panel	2 3/16" - 4 9/16"
Ⓣ Height from top of front panel to top of chassis	5/16"
Ⓤ Ventilation gaps between panels	1/4"
Ⓦ Height of toekick panel	2 13/16" - 5"
Ⓧ Depth of toekick recess	1 1/2" - 4"
Ⓨ Height of adjustable levelling feet	3/8" - 2 11/16"
Ⓩ Maximum extension of drawer from front datum	21 9/16"

* includes mounted feet

Minimum Clearances	in
Height of cavity	min 32 5/16"
Width of cavity	23 5/8"
Depth of cavity	min 22 1/16"
Minimum clearance from a corner cupboard	1/2"

Note: Service outlet at rear extends both sides, hoses and cords can be routed to either or both.


INDICATES CABINETRY / PRODUCT DATUM -----
INDICATES CABINETRY CLEARANCES -----

DATE: **07.09.2016**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit www.fisherpaykel.com

Fisher & Paykel

DATA SHEET



24" DOUBLE DISHDRAWER™

Model no:

DD24DAW9

(refer page 1 for imperial measurements)

Dimensions	mm
Ⓐ Overall height* of DishDrawer™	820 - 880
Ⓑ Overall width of DishDrawer™	599
Ⓒ Overall depth of DishDrawer™	573
Ⓓ Depth of chassis	553
Ⓔ Depth of front panel	20
Ⓕ Height of chassis	811
Ⓖ Height of drawer fronts	756
ⒼⒶ Height of upper front panel	393
ⒼⒷ Height of lower front panel	356
ⒼⒸ Height from floor to bottom of lower front panel	56-116
ⒼⒹ Height from top of front panel to top of chassis	8
ⒼⒺ Ventilation gaps between panels	7
ⒼⒻ Height of toekick panel	72 - 127
ⒼⒼ Depth of toekick recess	38 - 102
ⒼⒽ Height of adjustable levelling feet	9 - 69
ⒼⒾ Maximum extension of drawer from front datum	547

* includes mounted feet

Minimum Clearances	mm
Height of cavity	min 820
Width of cavity	600
Depth of cavity	min 560
Minimum clearance from a corner cupboard	13

Note: Service outlet at rear extends both sides, hoses and cords can be routed to either or both.

INDICATES CABINETRY / PRODUCT DATUM
INDICATES CABINETRY CLEARANCES

DATE: **07.09.2016**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit www.fisherpaykel.com

Fisher&Paykel