

FISHER & PAYKEL

DATA SHEET 30" Integrated Column Fridge / Freezer

Model nos:

RS3084SR1 / RS3084SRK1 / RS3084FRJ1 / RS3084FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS3084SL1 / RS3084SLK1 / RS3084FLJ1 / RS3084FLJK1

(refer page 2 for metric measurements)

Product Dimensions	in
Ⓐ Overall height of product	84"
Ⓑ Overall width of product	29 3/4"
Ⓒ Overall depth of product (excl. front door panels)	24"
Ⓓ Height from bottom datum to bottom of door	2" - 6"
Ⓔ Depth of toekick (excl. door front and toekick panels)	2 11/16" - 4"

Custom Panel Dimensions*	in
Ⓔ Height of door panel	77 7/8" - 81 7/8"
Ⓖ Width of door panel - single install Width of door panel - dual install	29 3/4" 29 13/16"
Ⓙ Height of custom toekick panel**	2" - 6"
Ⓚ Width of custom toekick panel	29 7/8"
Ⓛ Depth of custom panels	min 5/8" - max 1"
Maximum weight of door panel (including handle***)	66lbs

* Custom panels to be manufactured & fitted by cabinetmaker

** 3 15/16" tall stainless steel toekick panel available. Adjust the height of the door panel accordingly.


*** Door handle kit is available as an optional accessory.

Clearance Dimensions	in
Minimum cabinetry gap clearance from edge of door panel	1/8"
Overall height of cavity	84"
Overall width of cavity	30"
Minimum depth of cavity	25"
Minimum door clearance to adjacent wall (115° - full internal access)	16 1/2"
Minimum door clearance at 90° open, measured from front of door	32"

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



FISHER & PAYKEL

DATA SHEET 30" Integrated Column Fridge / Freezer

Model nos:

RS3084SR1 / RS3084SRK1 / RS3084FRJ1 / RS3084FRJK1

NOTE: Left hand hinge model is a mirrored version of image shown.

RS3084SL1 / RS3084SLK1 / RS3084FLJ1 / RS3084FLJK1

(refer page 1 for imperial measurements)

Product Dimensions	mm
Ⓐ Overall height of product	2134
Ⓑ Overall width of product	756
Ⓒ Overall depth of product (excl. front door panels)	610
Ⓓ Height from bottom datum to bottom of door	50 - 152
Ⓔ Depth of toekick (excl. door front and toekick panels)	68 - 101

Custom Panel Dimensions*	mm
Ⓔ Height of door panel	1978 - 2080
Ⓐ Width of door panel - single install Width of door panel - dual install	756 757.5
Ⓓ Height of custom toekick panel**	50 - 152
Ⓓ Width of custom toekick panel	759
Ⓐ Depth of custom panels	min 16 max 25
Maximum weight of door panel (including handle***)	30kg

* Custom panels to be manufactured & fitted by cabinetmaker

** 100mm tall stainless steel toekick panel available. Adjust the height of the door panel accordingly.

*** Door handle kit is available as an optional accessory.

Clearance Dimensions	mm
Minimum cabinetry gap clearance from edge of door panel	3
Overall height of cavity	2134
Overall width of cavity	762
Minimum depth of cavity	635
Minimum door clearance to adjacent wall (115° - full internal access)	419
Minimum door clearance at 90° open, measured from front of door	813

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

