



CUSTOM PANELS



FRONT VIEW



PROFILE VIEW

36" ActiveSmart™ Built-in Refrigerator

Model no:
RS36A80J1

Product Dimensions	in
Ⓐ Overall height of fridge	79 27/32"
Ⓑ Overall width of fridge	35 1/32"
Ⓒ Depth of fridge front panels (excl. handles)*	3/4"
Ⓓ Overall depth of fridge (excl. front door panels)	23 3/4"
Ⓔ Height from bottom datum to top of toekick	4"
Ⓕ Depth of toekick measured from front of door panels*	4 3/4"
Ⓖ Depth of door (widest opening) measured from front of cabinetry	18 29/32"
Ⓗ Depth of drawer (open) measured from front of cabinetry*	14 3/16"
Ⓘ Minimum door clearance** to adjacent wall (115° - full internal access)*	12 13/32"

* Door panels to be manufactured and fitted by cabinetmaker, thickness min 5/8" - max 3/4".

** Measured from front cabinetry edge.

Custom Panel Dimensions	in
Ⓙ Height of top door panel	45 9/32" - 49 9/32"
Ⓚ Width of top door panel	17 3/4"
Ⓛ Gap between top door panels	5/32"
Ⓜ Height of bottom drawer panel	28 13/32" - 30 13/32"
Ⓝ Width of bottom drawer panel	35 21/32"
Ⓞ Gap between top door panels and bottom drawer panel	5/32"
Ⓟ Height of toekick panel*	4" - 6"
Ⓠ Depth of custom panels	min 5/8" max 3/4"
Maximum weight of an individual top door panel	22 pounds
Maximum weight of bottom drawer panel	21 pounds

* The bottom grille can be reduced to allow for a higher toekick. Adjust the height of the bottom drawer panel accordingly.

Minimum Clearances	in
Minimum cabinetry gap clearance from edge of custom panels	5/32"
Overall height of cavity	80"/84"
Overall width of cavity	36"
Overall depth of cavity	24 3/4"





INDICATES PRODUCT DATUM

INDICATES MINIMUM CABINETRY CLEARANCES

DATE: 24.05.2015

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (3/32"). Please read the installation manual for detailed information on installing the product. www.fisherpaykel.com

Fisher & Paykel



36" ActiveSmart™ Built-in Refrigerator

Model no:

RS36A80J1

Product Dimensions	mm
Ⓐ Overall height of fridge	2028
Ⓑ Overall width of fridge	890
Ⓒ Depth of fridge front panels (excl. handles)*	19
Ⓓ Overall depth of fridge (excl. front door panels)	603
Ⓔ Height from bottom datum to top of toekick	102
Ⓕ Depth of toekick measured from front of door panels*	120
Ⓖ Depth of door (widest opening) measured from front of cabinetry	480
ⓓ Depth of drawer (open) measured from front of cabinetry*	360
Ⓣ Minimum door clearance** to adjacent wall (115° - full internal access)*	315

* Door panels to be manufactured and fitted by cabinetmaker, thickness min 16 - max 19.

** Measured from front cabinetry edge.

Custom Panel Dimensions	mm
Ⓛ Height of top door panel	1150 - 1252
Ⓧ Width of top door panel	451
Ⓨ Gap between top door panels	4
Ⓩ Height of bottom drawer panel	722 - 772
ⓐ Width of bottom drawer panel	906
ⓑ Gap between top door panels and bottom drawer panel	4
ⓔ Height of toekick panel*	101 - 152
ⓓ Depth of custom panels	min 16 max 19
Maximum weight of an individual top door panel	10 kg
Maximum weight of bottom drawer panel	11 kg

* The bottom grille can be reduced to allow for a higher toekick. Adjust the height of the bottom drawer panel accordingly.

Minimum Clearances	mm
Minimum cabinetry gap clearance from edge of custom panels	4
Overall height of cavity	2032/2134
Overall width of cavity	914
Overall depth of cavity	629

INDICATES PRODUCT DATUM -----
 INDICATES MINIMUM CABINETRY CLEARANCES -----

DATE: **24.05.2015**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (3/32"). Please read the installation manual for detailed information on installing the product. www.fisherpaykel.com

Fisher & Paykel