

FISHER & PAYKEL

DATA SHEET 610mm Integrated Column Fridge / Freezer

Model nos:

RS6121SRK1 / RS6121FRJK1
with Stainless Steel Door panel RD6121R10D, Handle AHD3-RD21
and Stainless Steel Toekick Panel AKRS06110

NOTE: Left hand hinge model is a mirrored version of image shown.

RS6121SLK1 / RS6121FLJK1
with Stainless Steel Door panel RD6121L10D, Handle AHD3-RD21
and Stainless Steel Toekick Panel AKRS06110

Product Dimensions	mm
Ⓐ Overall height of product	2134
Ⓑ Overall width of product	603
Ⓒ Depth of product front panels (excl. handles)	19
Ⓓ Overall depth of product (excl. front door panels)	610
Ⓔ Height from bottom datum to bottom of door	102
Ⓕ Depth of toekick (excl. door front and toekick panels)	68 - 101
Ⓖ Height of door panel	2029
Ⓜ Width of door panel	603
Ⓢ Height from bottom datum to bottom of handle	816
Ⓣ Height from bottom datum to top of handle	1668
Ⓚ Thickness of handles	16
Ⓛ Distance from side of fridge to the centre of handle	64
Ⓜ Depth of handle (measured from front of door)	41

Clearance Dimensions	mm
Minimum cabinetry gap clearance from edge of door panel	3
Overall height of cavity	2134
Overall width of cavity	610
Minimum overall depth (shallow) of cavity when services are located outside of cavity	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity	650
Minimum door clearance to adjacent wall (115° - full internal access)	356
Minimum door clearance at 90° open, measured from front of door	660

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

