

FISHER & PAYKEL

DATA SHEET

610mm Freezer + 762mm Fridge - Stainless Steel Integrated Columns

Model no:

RS6121FLJK1 + RS7621SRK1 shown

IMPORTANT!

For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Clearance Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	1372
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity*	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity*	650
Ⓓ Width of supply area behind freezer	610
Ⓔ Width of supply area behind fridge	762
Ⓕ Height of supply area	229
Ⓖ Height at sides of supply area	127
Ⓗ Width from side of supply area	13
Ⓘ Combined width in from side of supply areas	25
⓵ Depth of supply area	25
Minimum door cabinetry gap clearance	3


Optional Stainless Steel Panel Dimensions	mm
Ⓚ Height of door panel	2029
Ⓛ Width of freezer door panel	610
Ⓜ Width of fridge door panel	751
Ⓝ Depth of door panels	19
Ⓞ Height of toekick panel	100
Ⓟ Width of toekick panel	1368

*Connections may be located in an adjacent cabinet to either side of the fridge.

HANDLES: Handle Kits are sold separately. Shown with handle kit ADH3-RD21. Other style options available.

DATE: **10.10.2018**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



ISO VIEW OF 1372mm CAVITY
(610mm + 762mm)