

## 900mm CoolDrawer™ Multi-Temperature Refrigerator

Model no:

**RB90S64MKIW1**


**RB36S25MKIW** (refer page 2 for imperial measurements)

Product Dimensions	mm
Ⓐ Overall height* of CoolDrawer™**	640
Ⓑ Overall width* of CoolDrawer™	855
Ⓒ Depth of CoolDrawer™ chassis (includes power terminal)	557
Ⓓ Height from bottom datum to bottom of drawer front	187
Ⓔ Height from bottom datum to top of drawer front	635
Ⓕ Width of drawer front	805
Ⓖ Depth of drawer front	45
Ⓗ Depth of drawer (open) measured from front datum	520

\* Does not include the custom door panel or handle to be manufactured and fitted by cabinetmaker.

Minimum Clearances	mm
Minimum inside height of cavity from bottom datum*	665
Minimum inside width of cabinetry	864
Minimum inside depth of cavity from front datum	560

\* Minimum internal height of cabinetry can be 644 mm if outlet duct is not used. Please refer to installation manual for details.



DATE: 11.02.2013

IMPORTANT NOTE: Throughout this guide, dimensions may vary by  $\pm 2\text{mm}$  ( $3/32''$ ). Please read the installation manual for detailed information on installing the product. [www.fisherpaykel.com](http://www.fisherpaykel.com)

**36" CoolDrawer™ Multi-Temperature Refrigerator**


Model no:  
**RB90S64MKIW1** (refer page 1 for metric measurements)  
**RB36S25MKIW**

Product Dimensions	in
Ⓐ Overall height* of CoolDrawer™**	25-3/16"
Ⓑ Overall width* of CoolDrawer™	33-21/32"
Ⓒ Depth of CoolDrawer™ chassis (includes power terminal)	21-15/16"
Ⓓ Height from bottom datum to bottom of drawer front	7-3/8"
Ⓔ Height from bottom datum to top of drawer front	25"
Ⓕ Width of drawer front	31-11/16"
Ⓖ Depth of drawer front	1-25/32"
Ⓗ Depth of drawer (open) measured from front datum	20-15/32"

\* Does not include the custom door panel or handle to be manufactured and fitted by cabinetmaker.

Minimum Clearances	in
Minimum inside height of cavity from bottom datum*	26-3/16"
Minimum inside width of cabinetry	34-1/32"
Minimum inside depth of cavity from front datum	22-1/16"

\* Minimum internal height of cabinetry can be 25-11/32" if outlet duct is not used. Please refer to installation manual for details.



INDICATES CABINERY CARCASS DATUM -----  
 INDICATES MINIMUM CABINERY CLEARANCES - - - - -

DATE: 22.04.2013

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (3/32"). Please read the installation manual for detailed information on installing the product. [www.fisherpaykel.com](http://www.fisherpaykel.com)