QUICK REFERENCE GUIDE > RDV2-488-L_N
Date: 04.04.2024 > 1

Dual Fuel Range, 48", 8 Burners

Series 9 | Professional

Stainless Steel | LPG




A striking addition to your kitchen, with eight powerful gas burners and two ovens with a combined capacity of 6.9 cu ft.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two convection oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	47 7/8"
Depth	29 1/8"



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R48

Burner ratings

Maximum burner power	19000 BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front centre (2)	15000BTU
Power front left	19000BTU
Power front right	19000BTU

QUICK REFERENCE GUIDE > RDV2-488-L_N
Date: 04.04.2024 > 2

Total cooktop power	120000 BTU
Capacity	
Shelf positions	5
Shelf positions (main oven)	5
Shelf positions (second oven)	5
Cleaning	
Pyrolytic self-clean	•
Controls	
Electric circuit	4 wire
Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (LPG)	11" to 14" W.C
Oven features	
Auto re-ignition system	•
Internal light	•
Oven performance	
Bake power	4600
Broil	3600W
Main oven - True convection	2500W
Power requirements	

	60Hz
Product dimensions	
Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	47 7/8"
Rangetop features	
Sealed range top	•
Vent trim included	•
Safety	
Full extension telescopic	•
Secondary oven features	
Broil	•
	•
Concealed element	
Concealed element Electronic oven control	•
Electronic oven control	•
Electronic oven control Internal light	
Electronic oven control Internal light Secondary oven functions	•
Electronic oven control Internal light Secondary oven functions Bake	

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and

QUICK REFERENCE GUIDE > RDV2-488-L_N
Date: 04.04.2024 > 3

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN / Guide d'installation FR



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com