

Gas Range, 30", 5 Burners

Series 7 | Professional

Natural gas | Stainless Steel



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Gas oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Width	29 7/8"
Depth	29 1/8"

FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 22,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking flexibility

<>

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

Easy to clean

<>

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories

Square handle option	AH-R30
----------------------	--------

Capacity

Capacity total (AHAM)	4.6cu ft
Capacity usable (AHAM)	3.4cu ft
Shelf positions	5

Total capacity	4.6cu ft
Usable capacity	3.4cu ft

Cleaning

Dishwasher proof trivets	•
--------------------------	---

Controls

Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	1/2 NPT, min. 5/8" flex line
Supply Pressure (natural gas)	6" to 9" W.C

Installation Dimensions

Height (excluding vent trim)	35 3/4 - 36 3/4"
------------------------------	------------------

Oven features

Broil pan	•
Electronic oven control	•
Full extension telescopic	•
Infrared Broiler	•
Internal light	•
Titanium coated, illuminated	•

Oven functions

Bake	•
Broil	•
Convection bake	•
Number of functions	4

Slow cook •

Oven performance

Bake	28000 BTU
Bake power	21,000 BTU
Broil power	18,500 BTU

Power requirements

Amperage	15A
Rated current	15A
Supply frequency	60Hz

Product dimensions

Depth	29 1/8"
Width	29 7/8"

Rangetop features

Sealed Dual Flow Burners™	5
Sealed range top	•
Vent trim included	•

Rangetop Performance

Max burner power	23,500 BTU
Power back left	18,500 BTU
Power back right	18,500 BTU
Power centre	23,500 BTU
Power front left	18,500 BTU
Power front right	18,500 BTU
Total cooktop power	97,500 BTU

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional)

Safety

ADA compliant	•
Full extension telescopic	•

SKU 82006

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

↓	User Guide
↓	User Guide
↓	Guide D'Utilisation
↓	Installation Guide
↓	Installation Guide
↓	Installation Guide
↓	Guide D'Installation



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 W www.fisherpaykel.com