PRELIMINARY SPECIFICATION GUIDE

WALL RANGEHOOD





OVERVIEW

Designed to complete the Contemporary kitchen, these wall box chimney rangehoods are made from quality stainless steel and sleek black glass. With four fan speeds. Powerful extraction quickly removes odours and steam. Enjoy seamless operation with Wi-Fi enabled remote control.

MODELS

Wall Rangehood, 24", Box Chimney HC24DCXB4

Wall Rangehood, 30", Box Chimney HC30DCXB4

Wall Rangehood, 36", Box Chimney HC36DCXB4

FEATURES

- Sleek black glass finish with stainless steel frame
- ② Wi-Fi enabled for remote control and notifications through the SmartHQ[™] app
- 3 Edge-to-edge extraction
- 4 Bicolour LEDs 3K and 4K
- 5 Intuitive touch controls
- 6 Four fan speeds
- O Auto off timer function
- 8 Dishwasher-safe anti-drop aluminium filters
- 9 6 inch diameter duct
- (i) Recirculation options available

SERIES & STYLE

Series 7 Contemporary Style

ACCESSORIES

- Chimney Extension
- ② Recirculating Diverter
- 3 Recirculation Carbon Filter
- 4 Aluminium Filter

PRELIMINARY SPECIFICATION GUIDE


WALL RANGEHOOD, 24"


SPECIFICATIONS


HC24DCXB4		
H 25" - 40 3/4" x W 23 9/16" x D 19 11/16"		
Consult the cooktop installation guide for details of the required installation height of the rangehood		
120 V, 60 Hz		
3 pin plug		
9-Watt LED lightstrip		

PRODUCT DIMENSIONS

ATTACHMENT DIMENSIONS







		inch
<u>A</u>	Lower rangehood attachment point width	16 9/16
В	Lower rangehood attachment point height	1 7/16
©	Upper rangehood attachment point height	11 1/4
(D)	Chimney bracket attachment point height	22

PRELIMINARY SPECIFICATION GUIDE


WALL RANGEHOOD, 30"


SPECIFICATIONS

Model No.	HC30DCXB4
Dimensions	H 25" - 40 3/4" x W 29 3/4" x D 19 11/16"
Minimum distance above cooktops	Consult the cooktop installation guide for details of the required installation height of the rangehood
Electrical	
Supply	120 V, 60 Hz
Outlet	3 pin plug
Light source	
Туре	9-Watt LED lightstrip

PRODUCT DIMENSIONS

ATTACHMENT DIMENSIONS





· ·		13/10	6" <u>*</u>	9 13/16"		
7				9 1/4"		
0	9	В		9 13/16"		
1		<u> </u>	+	•	*	
				BACK VIEW		

		inch
(A)	Lower rangehood attachment point width	16 9/16
B	Lower rangehood attachment point height	1 7/16
©	Upper rangehood attachment point height	11 1/4
(D)	Chimney bracket attachment point height	22

PRELIMINARY SPECIFICATION GUIDE


WALL RANGEHOOD, 36"

SPECIFICATIONS


Model No.	HC36DCXB4
Dimensions	H 25" - 40 3/4" x W 35 3/8" x D 19 11/16"
Minimum distance above cooktops	Consult the cooktop installation guide for details of the required installation height of the rangehood
Electrical	
Supply	120 V, 60 Hz
Outlet	3 pin plug
Light source	
Туре	9-Watt LED lightstrip

PRODUCT DIMENSIONS

ATTACHMENT DIMENSIONS



		inch
A	Maximum overall height of rangehood	25
В	Minimum overall height of rangehood	40 3/4
©	Overall width of rangehood	35 3/8
(D)	Overall depth of rangehood	19 11/16
E	Diameter of ducting outlet	6



		inch
(A)	Lower rangehood attachment point width	22 13/16
В	Lower rangehood attachment point height	1 7/16
©	Upper rangehood attachment point height	11 1/4
(D)	Chimney bracket attachment point height	22