QUICK REFERENCE GUIDE > CPV2-364GDN N Date: 02.05.2024 > 1

# Gas Rangetop, 36", Griddle

Series 9 | Professional

Stainless Steel | Natural gas




A powerful six burner rangetop with professional styling and the additional cooking flexibility of a stainless steel griddle.

- Your burners can deliver anything from very high 23,500 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- The stainless steel griddle is great for cooking anything from pancakes to bacon, grilled cheese to quesadillas

# **DIMENSIONS**

Height	8 5/16"
Width	35 7/8"
Depth	28"



### **FEATURES & BENEFITS**

# Perfect Heat

Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### **Precise Control**

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

# Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. Heavyweight stainless steel griddles can be set to desired temperatures and then maintained evenly across the entire griddle surface.

## Easy cleaning

These rangetops have sealed burners and a single sheet cooking surface which, combined with a commercial-style stainless steel finish and dishwasher-safe grates, allow easy cleaning.

## INFORMATION AT A GLANCE

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

# **Complementary Design**

Built to last with distinctive, bold styling, this rangetop is designed to match the Fisher & Paykel Professional style family of appliances.

## **SPECIFICATIONS**

Burner ratings	
Max burner power	Yes
Power back left	18,500 BTU
Power back right	18,500 BTU
Power front left	23,500 BTU
Power front right	18,500 BTU
Power griddle	18,000 BTU
Total cooktop power	97,000 BTU

#### Controls

Metal illuminated dials

# **Gas Requirements**

Fitting and pipe ½ NPT, min. 5/4" ☐ flex line

QUICK REFERENCE GUIDE > CPV2-364GDN N Date: 02.05.2024 > 2

Supply Pressure (natural gas)	6" to 9" W.C
Performance	
Sealed Dual Flow Burners™	4
Sealed cooking surface	•
Simmer on all burners	140°F
Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	28"
Height	8 5/16"
Width	35 7/8"
Recommended Back Guards	Ventilation
Combustible situation	BGCV2-3036H
Minimum CFM	600 BTU
Non combustible situation	BGCV2-3036 / BGCV2-1236
Pro hood	VS36 / VS1236
Traditional hood	ES36

2 years

71386

Warranty Parts and labor

SKU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

#### Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

# Other product downloads available at fisherpaykel.com

User Guide



Service & Warranty



Installation Guide



Data Sheet Gas Cooktop



Planning Guide Gas Cooktop



24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com