

FISHER & PAYKEL

DATA SHEET 48" Professional Range

Model no:
RGV2-485GD-N, RGV2GD-485-L
RDV2-485GD-N, RDV2GD-485-L
 (refer page 3 for metric measurements)


| Product Dimensions | in |
|---|----------------------------|
| Ⓐ Overall height of range (from floor to cooktop, excluding grates and vent trim) | min 35 3/4" max 36 3/4" |
| Ⓑ Overall width of range | 47 7/8" |
| Ⓒ Overall depth of range (excluding handle and dials) | 29 1/8" |
| Ⓓ Depth from rear of chassis to cabinetry face - projecting | 25 1/8" |
| Ⓔ Depth from rear of chassis to cabinetry face - flush | 27 11/16" |
| Ⓕ Height from countertop to top of pan supports | 1 9/16" |
| Ⓖ Height from countertop to top of vent trim | 1 3/4" |
| Ⓗ Height from countertop to bottom of control panel | 7 3/4" |
| Ⓘ Height from countertop to top of door | 8 1/16" |
| Ⓚ Height from countertop to center of handle | 9 7/16" |
| Ⓛ Height from countertop to bottom of door | 28 7/8" |
| Ⓜ Height from countertop to bottom of chassis | 35 1/4" |
| Ⓝ Thickness of handles (not including standoffs) | 1 1/4" |
| Ⓞ Width of left handle (including standoffs) | 15 1/16" |
| Ⓟ Width of right handle (including standoffs) | 31 1/2" |
| Ⓠ Depth of handle (measured from front of door) | 3 1/16" |
| Ⓡ Depth of open door to cabinetry face - flush | 19 1/8" |
| Ⓢ Adjustable feet height | min 1/2" max 1 1/2" |

| Cavity Dimensions | in |
|--|----------------------------|
| Overall height of cavity | min 35 3/4" max 36 3/4" |
| Overall width of cavity | min 48" |
| Overall depth of cavity for projecting control panel | max 25 1/8" |
| Overall depth of cavity for flush control panel | max 27 11/16" |

INDICATES PRODUCT DATUM -----

DATE: **24.04.2018**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com



CABINET FACE FOR INSTALLATION WITH FLUSH CONTROL PANEL
 CABINET FACE FOR INSTALLATION WITH PROJECTING CONTROL PANEL

FISHER & PAYKEL

DATA SHEET 48" Professional Range


Model no:

RGV2-485GD-N, RGV2-485GD-L

RDV2-485GD-N, RDV2-485GD-L

(refer page 4 for metric measurements)

| Clearance Dimensions | in |
|--|------------|
| Ⓐ Minimum width of ventilation hood installed above range - not shown* | 48" |
| Ⓑ Minimum vertical distance between countertop and cabinet extending above counter | 18" |
| Ⓒ Minimum clearance from left and right edge of range to nearest vertical combustibile surface | 12" |
| Ⓓ Minimum clearance from cooking surface to: - combustibile surface centered above the cooking surface - non-combustibile surface centered above the cooking surface | 54" 30" |
| Ⓔ Maximum overall depth of overhead cabinetry | 13" |



INDICATES CABINETRY CLEARANCES -----

INDICATES PRODUCT DATUM -----

DATE: **24.04.2018**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL


DATA SHEET 48" Professional Range

Model no:

RGV2-485GD-N, RGV2-485GD-L

RDV2-485GD-N, RDV2-485GD-L

(refer page 1 for imperial measurements)



| Product Dimensions | mm |
|---|--------------------|
| Ⓐ Overall height of range (from floor to cooktop, excluding grates and vent trim) | min 908 max 933 |
| Ⓑ Overall width of range | 1216 |
| Ⓒ Overall depth of range (excluding handle and dials) | 740 |
| Ⓓ Depth from rear of chassis to cabinetry face - projecting | 638 |
| Ⓔ Depth from rear of chassis to cabinetry face - flush | 703 |
| Ⓘ Height from countertop to top of pan supports | 40 |
| Ⓚ Height from countertop to top of vent trim | 45 |
| Ⓛ Height from countertop to bottom of control panel | 196 |
| Ⓚ Height from countertop to top of door | 204 |
| Ⓛ Height from countertop to centre of handle | 240 |
| Ⓚ Height from countertop to bottom of door | 734 |
| Ⓛ Height from countertop to bottom of chassis | 895 |
| Ⓚ Thickness of handles (not including standoffs) | 32 |
| Ⓛ Width of left handle (including standoffs) | 393 |
| Ⓚ Width of right handle (including standoffs) | 801 |
| Ⓛ Depth of handle (measured from front of door) | 77 |
| Ⓚ Depth of open door to cabinetry face - flush | 486 |
| Ⓚ Adjustable feet height | min 13 max 38 |

| Cavity Dimensions | mm |
|--|--------------------|
| Overall height of cavity | min 908 max 933 |
| Overall width of cavity | min 1219 |
| Overall depth of cavity for projecting control panel | max 638 |
| Overall depth of cavity for flush control panel | max 703 |

INDICATES PRODUCT DATUM

DATE: 24.04.2018

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com




FISHER & PAYKEL

DATA SHEET 48" Professional Range

Model no:
RGV2-485GD-N, RGV2-485GD-L
RDV2-485GD-N, RDV2-485GD-L
(refer page 2 for imperial measurements)

| Clearance Dimensions | mm |
|---|------|
| Ⓐ Minimum width of ventilation hood installed above range - not shown* | 1219 |
| Ⓑ Minimum vertical distance between countertop and cabinet extending above counter | 457 |
| Ⓒ Minimum clearance from left and right edge of range to nearest vertical combustible surface | 305 |
| Ⓓ Minimum clearance from cooking surface to: - combustible surface centred above the cooking surface | 1372 |
| - non-combustible surface centred above the cooking surface | 762 |
| Ⓔ Maximum overall depth of overhead cabinetry | 330 |



0 100 200 400 millimetres

INDICATES CABINETRY CLEARANCES -----
INDICATES PRODUCT DATUM -----

DATE: **24.04.2018**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com