QUICK REFERENCE GUIDE > RDV3-485GD-L Date: 04.04.2024 > 1

Dual Fuel Range, 48", 5 Burners with Griddle, Selfcleaning, LPG

Series 9 | Professional

Stainless Steel | LPG




With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Gas cooktop with a griddle and five burners that deliver up to 19,000 BTU for fast boiling
- 6.9 cu ft total oven capacity across two oven cavities

Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

Height	35 3/4 - 36 3/4
Width	47 7/8'
Depth	29 1/8



FEATURES & BENEFITS

Cook with confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal

visibility while cooking.

Generous capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop power

Sealed dual flow burners deliver cooktop power up to 19,000 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy to clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories

Adjustable feet covers

Branded coin end cap

•

QUICK REFERENCE GUIDE > RDV3-485GD-L Date: 04.04.2024 > 2

Accessories (sold separately)		Electric circuit	4 wire	Maxi Broil	•
Square handle option	AH-R48	High resolution display	•	Number of functions	15
		Metal illuminated dials	•	Pastry bake	•
Burner ratings		Multi-language interface	•	Pizza bake	•
Maximum burner power	19000 BTU	Precise cooking with food	•	Rapid proof	•
Power back left	11500BTU	Recipe and food based	•	Roast	•
Power back right	11500BTU	Sabbath mode	•	Slow cook	•
Power centre	19000BTU	Tilting touch screen interface	•	True convection	•
Power front left	15000BTU	Wi-Fi connectivity	•	Warm	•
Power front right	15000BTU				
Power griddle	24000BTU	Gas Requirements Oven performance		Oven performance	
Total cooktop power	96000 BTU	Fitting and pipe	½ NPT, min. %" 🛭 flex line	Bake power	4600
		Supply Pressure (LPG)	11" to 14" W.C	Broil	3600W
Capacity				Main oven - True convection	2500W
Shelf positions (main oven)	5	Oven features			
Shelf positions (second oven)	5	Auto re-ignition system	•	Power requirements	
Total capacity (main oven)	4.8cu ft	Concealed element	•	Amperage	50A
Total capacity second oven	2.1cu ft	Electronic oven control	•	Rated current	50A
Usable capacity (main oven)	3.8cu ft	Full extension telescopic	•	Supply frequency	60Hz
		Internal light	•		
Cleaning		Titanium coated, illuminated	•	Product dimensions	
Easy clean porcelain basepan	•			Depth	29 1/8"
Pyrolytic self-clean	•	Oven functions		Height	35 3/4 - 36 3/4"
		Air fry	•	Width	47 7/8"
Consumption		Bake	•		
Energy usage	470kWh/year	Classic bake	•	Rangetop features	
		Clean	•	Sealed range top	
Controls		Convection Broil	•	Vent trim included	
Dial with illuminated halo	•	Convection bake	•		
Dual control oven dials	•	Dehydrate	Dehydrate • Recommended Back Guards Ventilation		

QUICK REFERENCE GUIDE > RDV3-485GD-L Date: 04.04.2024 > 3

Combustible situation BGRV3-3048H Non combustible situation BGRV2-3048 / BGRV2-1248 Recommended hood HCB48-12_N (48"" Safety ADA compliant Secondary oven features 3/4 Extension racks 2 Concealed element Electronic oven control Food probe Internal light Secondary oven functions Air frv Bake Classic bake Convection bake Convection broil Maxi broil Number of secondary oven 11 Pastry bake Pizza bake Rapid proof Roast Warm

81895

SKU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

<u></u>

Guide d'utilisation FR



Guide d'utilisation FR



User Guide EN



Service & Warranty



Energy Label



Installation Guide EN



Guide d'installation FR



Specification Guide Dual Fuel Range



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



Planning Guide Professional Style Dial/Handle Accessories



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com