

48" Series 9 5 Burner Gas with Griddle Rangetop, Natural Gas

Professional



A powerful five burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Your burners can deliver anything from very high 23,500 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from pancakes to bacon, grilled cheese to quesadillas
- Made from quality materials and real stainless steel

DIMENSIONS

| | |
|--------|----------|
| Height | 8 5/16 " |
| Width | 47 7/8 " |
| Depth | 28 " |

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design Quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

SPECIFICATIONS

Accessories (sold separately)

| | |
|------------------------------------|--------------|
| Dial kit Professional, Brass | ADLP3CP485BA |
| Dial kit Professional, Dark Copper | ADLP3CP485DC |

Burner ratings

| | |
|----------------------|-------------|
| Maximum burner power | Yes |
| Power back left | 18,500 BTU |
| Power back right | 18,500 BTU |
| Power front centre | 23,500 BTU |
| Power front left | 18,500 BTU |
| Power front right | 18,500 BTU |
| Power griddle | 24,000 BTU |
| Total cooktop power | 121,500 BTU |

Cleaning

| | |
|------------------------------|---|
| Easy clean porcelain basepan | • |
|------------------------------|---|

Controls

| | |
|--|---|
| Metal illuminated dials | • |
| Star K Certification | • |
| Titanium coated, illuminated metal dials | • |

Gas Requirements

| | |
|------------------|--------------------------|
| Fitting and pipe | ½ NPT, min. ⅝" flex line |
|------------------|--------------------------|

Supply Pressure (natural gas) **6" to 9" W.C**

SKU **82983**

Performance

Sealed cooking surface •
 Sealed Dual Flow Burners™ **5**
 Sealed range top •
 Simmer on all burners **140 °F**

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) DWG
- [↓](#) DWG
- [↓](#) DWG
- [↓](#) DXF
- [↓](#) DXF
- [↓](#) DXF
- [↓](#) Archicad
- [↓](#) Data Sheet - Backguard-BGCV2-1248 (English)
- [↓](#) Data Sheet - Backguard-BGCV2-3048 (English)
- [↓](#) Data Sheet - Backguard-BGCV2-3048H (English)
- [↓](#) Installation Guide (English)
- [↓](#) Installation Guide (Canadian French)
- [↓](#) Revit
- [↓](#) Rhino
- [↓](#) Right To Repair Declaration (English, Canadian French)
- [↓](#) SketchUp
- [↓](#) User Guide (English)
- [↓](#) User Guide (Canadian French)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
 T 1.888.936.7872 Wwww.fisherpaykel.com

Power requirements

Amperage **15 A**
 Supply frequency **60 Hz**
 Supply voltage **120 V**

Product dimensions

Depth **28 "**
 Height **8 5/16 "**
 Width **47 7/8 "**

Recommended Back Guards Ventilation

Combustible situation **BGCV2-3048H**
 Non combustible situation **BGCV2-3048 / BGCV2-1248**
 Pro hood **HCB48-12_N**

Zone ratings

Front right **18500 BTU**