QUICK REFERENCE GUIDE > RGV3-488-N

# Gas Range, 48", 8 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- · Made from quality materials and real stainless steel

## **DIMENSIONS**

Height	35 3/4 - 36 3/4
Width	47 7/8
Depth	29 1/8

## **FEATURES & BENEFITS**

## **Generous Capacity**

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

## **Cooktop Power**

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

## Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

#### **EASY TO CLEAN**

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

## **Design Quality**

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

## **Total Control**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

## **SPECIFICATIONS**

## Burner ratings

Maximum burner power	23500 BT
Power back centre	18500BT
Power back centre (2)	18500BT
Power back left	18500BT
Power back right	18500BT
Power front centre	18500BT
Power front centre (2)	18500BT
Power front left	23500BT
Power front right	23500BT
Total cooktop power	158000 BT

## Capacity

Shelf positions	!
Total capacity (main oven)	5.3cu f
Total capacity second oven	2.4cu f
Usable capacity (main oven)	3.9cu f

## Cleaning

Easy clean porcelain basepan	
------------------------------	--

#### Controls

Electric circuit	3 wire
Metal illuminated dials	•

#### Gas Requirements

Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (natural gas)	6" to 9" W.C

## Oven features

QUICK REFERENCE GUIDE > RGV3-488-N

Auto re-ignition system	•	
Electronic oven control	•	
Full extension telescopic	•	
Internal light	•	
Titanium coated, illuminated	•	
Oven functions		
Bake	•	
Broil	•	
Convection bake	•	
Slow cook	•	
Oven performance		
Main oven - Bake power	28,000 BTU	
Main oven - Broil power	18,500 BTU	
Secondary oven - Bake power	18,000 BTU	
Power requirements		
Amperage	15A	
Rated current	15A	
Supply frequency	60Hz	
Product dimensions		
Depth	29 1/8"	
Depth (excluding handles)	29 1/8"	
Height	35 3/4 - 36 3/4"	
Width	47 7/8'	
Rangetop features		
Sealed range top		

Recommended Back Guards	s Ventilation
Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48" Professional
Safety	
ADA compliant	•
Full extension telescopic	•
Secondary oven features	
3/4 Extension racks	2
Electronic oven control	•
Internal light	•
Secondary oven functions	
Bake	•
Convection bake	•
Number of secondary oven	4
Proof	•
Slow cook	•
SKU	81994

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model

currently available. Fisher & Paykel Appliances Ltd 2020

## Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > RGV3-488-N Date: 02.05.2024 > 3

# Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Installation Guide



## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com