QUICK REFERENCE GUIDE > RDV3-486GD-L Date: 02.05.2024 > 1

Dual Fuel Range, 48", 6 Burners with Griddle

Series 9 | Professional

Stainless Steel | LPG



With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe
- Gas cooktop with a griddle and six burners that deliver up to 19,000 BTU for fast boiling
- 6.9 cu ft total oven capacity across two oven cavities
- Use the food probe to monitor your cooking real time

DIMENSIONS

 Height
 35 3/4 - 36 3/4"

 Width
 47 7/8"

 Depth
 29 1/8"

FEATURES & BENEFITS

COOK WITH CONFIDENCE

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

GENEROUS CAPACITY

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

COOKTOP POWER

Sealed dual flow burners deliver cooktop power up to 19,000 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design Quality

This range has craftsmanship in every detail, with real stainless

steel, cast-iron trivets, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories Adjustable feet covers Branded coin end cap Telescopic sliding runners • Accessories (sold separately) Square handle option AH-R48 Burner ratings Maximum burner power 19000 BTU

Power back centre 13000BTU Power back left 13000BTU Power back right 13000BTU 15000BTU Power front centre Power front left 19000BTU Power front right 15000BTU 15000BTU Power griddle Total cooktop power 103000 BTU

Capacity

QUICK REFERENCE GUIDE > RDV3-486GD-L Date: 02.05.2024 > 2

Shelf positions (main oven)	5	Full extension telescopic			
				Product dimensions	
Shelf positions (second oven)	5	Internal light	•	Depth	29 1/8"
Total capacity (main oven)	4.8cu ft	Large broil pan	•	Height	35 3/4 - 36 3/4"
Total capacity second oven	2.1cu ft	Self-clean proof side racks	•		
Usable capacity (main oven)	3.8cu ft	True convection	•	Width	47 7/8"
				Damastan fasturas	
Cleaning		Oven functions		Rangetop features	
Easy clean porcelain basepan	•	Air fry	•	Sealed range top	•
Pyrolytic proof shelf runners	•	Bake	•	Vent trim included	•
		Broil	•		
Controls		Classic bake	•	Rangetop Performance	
Dial with illuminated halo	•	Clean	•	Number of burners	6
Dual control oven dials	•	Convection Broil	•		
High resolution display	•	Convection bake	•	Recommended Back Guards Ventilation	
Multi-language interface	•	Dehydrate	•	Combustible situation	BGRV3-3048H
Precise cooking with food	•	Maxi Broil	•	Non combustible situation	BGRV2-3048 / BGRV2-1248
Recipe and food based	•	Number of functions	15	Recommended hood	HCB48-12_N (48" Professional
Sabbath mode	•	Pastry bake	•		
Tilting touch screen interface	•	Pizza bake	•	Safety	
Wi-Fi connectivity	•	Rapid proof	•	ADA compliant	•
		Roast	•	Child lock	•
Gas Requirements		Slow cook	•		
Fitting and pipe	½ NPT, min. %" 🛭 flex line	True convection	•	Secondary oven features	
Supply Pressure (LPG)	11" to 14" W.C	Warm	•	3/4 Extension racks	2
				Concealed element	•
Oven features		Power requirements		Electronic oven control	•
Auto re-ignition system	•	Amperage	50A	Food probe	•
Concealed element	•	Rated current	50A	Internal light	•
Electronic oven control	•	Supply frequency	60Hz		
Food probe	•	Supply voltage	120/208, 120/240V	Secondary oven functions	

QUICK REFERENCE GUIDE > RDV3-486GD-L Date: 02.05.2024 > 3

Air fry	•
Bake	•
Classic bake	•
Convection bake	•
Convection broil	•
Maxi broil	•
Number of secondary oven	11
Pastry bake	•
Pizza bake	•
Rapid proof	•
Roast	•
Warm	•

Warranty

Parts and labor

SKU			82386

Limited 2 years

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy

Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN



Guide d'installation FR



Data Sheet Professional Range



Planning Guide Professional Style Dial/Handle Accessories



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com