QUICK REFERENCE GUIDE > RGV3-366-N

Gas Range, 36", 6 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Professional style with power. 23,500 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Gas oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4
Width	35 7/8
Depth	29 1/8

FEATURES & BENEFITS

Generous capacity

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

Cooktop Power

Sealed Dual Flow Burners[™] deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories (sold separately)

Square handle option	AH-R36
----------------------	--------

Burner ratings

Durner ratings	
Maximum burner power	23500 BTU
Power back centre	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front left	23500BTU
Power front right	23500BTU
Total cooktop power	121000 BTU

Capacity

Shelf positions	5
Total capacity	5.3cu ft
Usable capacity	4cu ft

Controls

minimum attendant

Electric circuit	3 Wire	•
Metal illuminated dials		•

Gas Requirements

Fitting and pipe	½ NPT, min. ¾" ⅓ flex lin
Supply Pressure (natural gas)	6" to 9" W.0

Oven features

Auto re-ignition system

•	•		
Broil pan			
Di Oli pari			

QUICK REFERENCE GUIDE > RGV3-366-N

Full extension telescopic	•
Infrared Broiler	•
Internal light	•
Titanium coated, illuminated	•
Oven functions	
Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•
Oven performance	
Bake power	28,000 BTU

Power requirements	
Amperage	

Rated current 15A
Supply frequency 60Hz

Product dimensions

Broil power

Depth 29 1/8"

Height 35 3/4 - 36 3/4"

Width 35 7/8"

Rangetop features

Sealed range top

Vent trim included

Recommended Back Guards Ventilation

Combustible situation BGRV3-3036H

Non combustible situation BGRV2-3036 / BGRV2-1236

Recommended hood HCB36-6_N (36" Professional

Safety

ADA compliant
Full extension telescopic

SKU 82002

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

18,500 BTU

15A

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Installation Guide

