Gas Cooktop, 30"

Series 7 | Professional

Stainless Steel | Natural gas



A powerful high-heat four burner with precision control and performance. Pair with any other appliance in our Professional range.

- Your burners can deliver anything from a high 20,000 BTU heat per burner for fast boiling, to a gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from quality materials and real stainless steel

DIMENSIONS

Height	5 1/2"
Width	30″
Depth	21″

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners[™] deliver cooktop power up to 20,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise control

From the highest to the lowest temperatures you get total control. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The self-locating grates focus the flame on the base of each pan, where it is most required. They are designed for easy and safe sliding of pans across the cooktop surface. For cooking variety, a wok ring accessory is also available.

Easy To Clean

These cooktops are easy to clean with a commercial-style stainless steel finish, sealed burners and a single sheet cooking surface.

Complementary design

Built to last with distinctive, bold styling, this cooktop is designed to match the Fisher & Paykel Professional style family of appliances.

SPECIFICATIONS

Burner ratings

Max burner power

Power back left	15,000 BTU
Power back right	15,000 BTU
Power front left	20,000 BTU
Power front right	15,000 BTU
Total cooktop power	65,000 BTU

Controls

Metal dials

Gas Requirements

Fitting and pipe	½ NPT, min. 5⁄8″ 🛛 flex line
Supply Pressure (natural gas)	6" to 9" W.C

Performance

Sealed Dual Flow Burners™	4
Sealed cooking surface	•
Simmer on all burners	140°F

Power requirements

Amperage	15A
Supply frequency	60Hz
Supply voltage	120V

Product dimensions

Downdraft

Depth	21″
Height	5 1/2"
Width	30″

Recommended Back Guards Ventilation

HD30

FISHER & PAYKEL

QUICK REFERENCE GUIDE > CDV3-304-N

Minimum CFM Pro hood	600 BTU HCB30-6 N
Traditional hood	ES30
Safety	
ADA compliant	
Warranty	
Parts and labour	2 years
SKU	82381

Other product downloads available at fisherpaykel.com

↓ User Guide
↓ Guide d'utilisation FR
↓ Service & Warranty
↓ Installation Guide
↓ Guide d'installation FR

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

A PEACE OF MIND SALE



24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com