QUICK REFERENCE GUIDE > DD24SAX9 N

# Single DishDrawer™ Dishwasher

Series 7 | Contemporary

Stainless Steel




A compact size to fit anywhere, room to wash a half load, and less bending.

- Six wash programs to suit any load, from Delicate to Heavy
- American Disabilities Act (ADA) compliant, this can be installed at an accessible height for loading and unloading.

### **DIMENSIONS**

| Height | 16 1/8"  |
|--------|----------|
| Width  | 23 9/16" |
| Depth  | 22 9/16" |



### **FEATURES & BENEFITS**

### Ease of use

DishDrawer™ Dishwashers are as easy to open and close as kitchen drawers and can be conveniently positioned at bench height for ease of loading and minimal bending.

### Flexible wash options

DishDrawer™ Dishwashers feature many programs including: Rinse, Fast, Delicate, Normal Eco, Normal and Heavy. These options allow the DishDrawer™ to wash everything from fine glass and crystal to heavily soiled pots and pans at the touch of a button.

### Complementary design

DishDrawer™ Dishwashers can be installed in any kitchen space and are designed to match the Fisher & Paykel family of kitchen appliances, with matching handles, premium styling and quality materials.

### Quiet performer

Running at a very low decibel rate, these DishDrawer™

Dishwashers do their job without making a fuss. The combination of intelligent technology and simple mechanics means greater reliability and excellent wash performance.

### **SPECIFICATIONS**

# Accessories Cutlery basket Capacity and loading Accommodates round plates

| Accommodates round plates       | •• |
|---------------------------------|----|
| Fixed height, foldable cupracks | •  |
| Fold down tines                 | •  |
| Place settings                  | 7  |

### Consumption

| Energy rating                | Energy star     |
|------------------------------|-----------------|
| Energy usage                 | 151kWh/year     |
| In-use energy carbon         | 55.3kgCO2e/year |
| Water usage (per wash cycle) | 1.81 gal        |
|                              |                 |

### Controls

| Electronic fault, | t/Diagnostic | • |
|-------------------|--------------|---|
| End of cycle be   | eeps         | • |

QUICK REFERENCE GUIDE > DD24SAX9 N Date: 04.04.2024 > 2

| Reylock Rinse aid indicator light  Wi-Fi connectivity  Features  Fan assisted drying Flood protection Flow through detergent Motor type BLDC Quiet operation SmartDrive™ technology  Performance Noise emissions  AddBA  Power requirements  Amperage Fated current Supply frequency Supply voltage  Product dimensions Depth Pethology  Safety and compliance ADA compliant  • | Energy saving delay start | •          |
|---|---------------------------|------------|
| Features Fan assisted drying Flood protection Flow through detergent Motor type BLDC Quiet operation SmartDrive™ technology  Performance Noise emissions  43dBA  Power requirements Amperage Electric circuit 3 wire Rated current 15A Supply frequency Supply voltage  Product dimensions Depth 16 1/8″ Width 23 9/16″  Safety and compliance                                  | Keylock                   | •          |
| Features  Fan assisted drying  Flood protection  Flow through detergent  Motor type  Guiet operation  SmartDrive™ technology  Performance  Noise emissions  AddBA  Power requirements  Amperage  Fated current  Supply frequency  Supply voltage  Product dimensions  Depth  Performance  16 1/8″  Width  Safety and compliance   | Rinse aid indicator light | •          |
| Fan assisted drying  Flood protection  Flow through detergent  Motor type  BLDC  Quiet operation  SmartDrive™ technology  Performance  Noise emissions  43dBA  Power requirements  Amperage  5A  Electric circuit  3 wire  Rated current  15A  Supply frequency  5upply voltage  100 - 120V  Product dimensions  Depth  22 9/16"  Height  16 1/8"  Width  Safety and compliance | Wi-Fi connectivity        | •          |
| Flood protection  Flow through detergent  Motor type  BLDC  Quiet operation  SmartDrive™ technology  Performance  Noise emissions  43dBA  Power requirements  Amperage  Fated current  Supply frequency  Supply voltage  Product dimensions  Depth  16 1/8"  Width  Safety and compliance   | Features                  |            |
| Flow through detergent  Motor type  BLDC Quiet operation  SmartDrive™ technology  Performance  Noise emissions  43dBA  Power requirements  Amperage  5A Electric circuit  3 wire Rated current  15A Supply frequency  50Hz Supply voltage  100 - 120V  Product dimensions  Depth  42 9/16"  Height  16 1/8"  Width  Safety and compliance                                       | Fan assisted drying       | •          |
| Motor type BLDC Quiet operation . SmartDrive™ technology .  Performance Noise emissions 43dBA  Power requirements Amperage 5A Electric circuit 3 wire Rated current 15A Supply frequency 60Hz Supply voltage 100 - 120V  Product dimensions Depth 22 9/16″ Height 16 1/8″ Width 23 9/16″  Safety and compliance   | Flood protection          | •          |
| Quiet operation SmartDrive™ technology  Performance Noise emissions  AdBA  Power requirements  Amperage 5A Electric circuit 3 wire Rated current 15A Supply frequency 5upply voltage  Product dimensions Depth 122 9/16" Height 16 1/8" Width 23 9/16"  Safety and compliance   | Flow through detergent    | •          |
| Performance Noise emissions  43dBA  Power requirements  Amperage Electric circuit 3 wire Rated current 15A Supply frequency Supply voltage  100 - 120V  Product dimensions Depth Height 16 1/8" Width 23 9/16"  Safety and compliance   | Motor type                | BLDC       |
| Performance Noise emissions  43dBA  Power requirements  Amperage 5A  Electric circuit 3 wire  Rated current 15A  Supply frequency 60Hz  Supply voltage 100 - 120V  Product dimensions  Depth 422 9/16"  Height 16 1/8"  Width 23 9/16"  | Quiet operation           | •          |
| Noise emissions  43dBA  Power requirements  Amperage 5A  Electric circuit 3 wire  Rated current 15A  Supply frequency 60Hz  Supply voltage 100 - 120V  Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"   | SmartDrive™ technology    | •          |
| Power requirements  Amperage 5A  Electric circuit 3 wire  Rated current 15A  Supply frequency 60Hz  Supply voltage 100 - 120V  Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"   | Performance               |            |
| Amperage 5A  Electric circuit 3 wire  Rated current 15A  Supply frequency 60Hz  Supply voltage 100 - 120V  Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"   | Noise emissions           | 43dBA      |
| Electric circuit 3 wire Rated current 15A Supply frequency 60Hz Supply voltage 100 - 120V  Product dimensions Depth 22 9/16" Height 16 1/8" Width 23 9/16"  Safety and compliance   | Power requirements        |            |
| Rated current 15A Supply frequency 60Hz Supply voltage 100 - 120V  Product dimensions Depth 22 9/16" Height 16 1/8" Width 23 9/16"  Safety and compliance   | Amperage                  | 5A         |
| Supply frequency 60Hz Supply voltage 100 - 120V  Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"  Safety and compliance  | Electric circuit          | 3 wire     |
| Supply voltage 100 - 120V  Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"  Safety and compliance  | Rated current             | 15A        |
| Product dimensions  Depth 22 9/16"  Height 16 1/8"  Width 23 9/16"  Safety and compliance   | Supply frequency          | 60Hz       |
| Depth 22 9/16" Height 16 1/8" Width 23 9/16"  Safety and compliance   | Supply voltage            | 100 - 120V |
| Height 16 1/8" Width 23 9/16"  Safety and compliance  | Product dimensions        |            |
| Width 23 9/16"  Safety and compliance   | Depth                     | 22 9/16"   |
| Safety and compliance   | Height                    | 16 1/8"    |
|   | Width                     | 23 9/16"   |
|   | Safety and compliance     |            |
|   | ADA compliant             |            |

| Limited 2 years  • • •        |
|-------------------------------|
|                               |
|                               |
| ·<br>·                        |
| •                             |
| •                             |
|                               |
|                               |
| •                             |
| 6                             |
|                               |
| 30kPa - 1000 kPa              |
| 3/8" to suit Male Compression |
| 82333                         |
|                               |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

# Other product downloads available at fisherpaykel.com



Quick Start Guide



Service & Warranty



Energy Label Single DishDrawer



User Guide DishDrawer™ Dishwasher EN



Installation Guide Single DishDrawer™ Dishwasher EN



Data Sheet Single DishDrawer™ Dishwasher



# A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com