QUICK REFERENCE GUIDE > HS60LXW4

Wall Rangehood, 60cm, Telescopic

Series 3 | Contemporary

White



The wall chimney rangehood has contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.


- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of 180m³/hr
- · Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

 Height
 181-185mm

 Width
 598mm

 Depth
 280 - 460mm



FEATURES & BENEFITS

Easy installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Simple to use

Intuitive controls responds to the touch of your finger. Two halogen spotlights provide clear illumination over the entire cooking surface.

Easy cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless integration

With the white glass front panel handles and a brushed stainless steel finish, this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories

40mm Stainless handle	792405 (included installed)
40mm white glass handle	792394 (included)
70mm Stainless handle	792399 (not included)
Aluminium filter	792391

Accessories (sold separately)

Eave ducting kit	PD-RHK125E
Handle required for	HS60 Part No.792399
Light bulb	791822
Recirculation carbon filter	792390
Roof ducting kit	PD-RHK125T
Side wall ducting kit	PD-RHK125W

Fan ratings

Maximum air movement	180m³/hi
Maximum sound rating	64dBA

Installation and cleaning

Dishwasher safe filters

QUICK REFERENCE GUIDE > HS60LXW4

Ducted	Top and back extraction	
Recirculation	Optional - top and back	
Performance		
Extraction type	Surface	
Fan speeds	2	
Filter type	Mesh	
Number of filters	2	
Power requirements		
Supply frequency	50Hz	
Supply voltage	220-240V	
Product dimensions		
Depth	280 - 460mm	
Height	181-185mm	
Width	598mm	
Product information		
Control type	Switch	
Ventilation features		
Light type	LED	
Warranty		
Parts and labour	2 years	
SKU	50015	
380	30013	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions.

Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1300 650 590 Wwww.fisherpaykel.com