Gas Range, 36", 6 Burners, I PG

Series 7 | Professional

Stainless Steel | LPG



Professional style with power. 17,000 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	35 7/8"
Depth	29 1/8″

FEATURES & BENEFITS

Generous capacity

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

Cooktop power

Sealed Dual Flow Burners[™] deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

EASY TO CLEAN

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

.

Accessories (sold separately)	
Square handle option	AH-R36
Burner ratings	
Maximum burner power	17000 BTU
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	17000BTU
Power front right	17000BTU
Total cooktop power	88000 BTU
Capacity	
Shelf positions	5

Shelf positions	5
Total capacity	5.3cu ft
Usable capacity	4cu ft

Controls	
Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	½ NPT, min. 5%" 🛛 flex line
Supply Pressure (LPG)	11" to 14" W.C

Oven features

Auto re-ignition system

Broil pan

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RGV3-366-L

Electronic oven control	
Full extension telescopic	
Infrared Broiler	
Internal light	
Titanium coated, illuminated	

Oven functions

Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•

Oven performance

Bake power	21,500 BTU
Broil power	19,000 BTU

Power requirements

Amperage	15A
Rated current	15A
Supply frequency	60Hz

Product dimensions

Depth	29 1/8″
Height	35 3/4 - 36 3/4"
Width	35 7/8"

Rangetop features

Sealed range top

Vent trim included

Recommended Back Guards Ventilation	
Combustible situation	BGRV3-3036H
Non combustible situation	BGRV2-3036 / BGRV2-1236

HCB36-6_N (36" Professional

82003

Recommended hood

Safety ADA compliant Full extension telescopic SKU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com





A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com