QUICK REFERENCE GUIDE > RGV3-488-N

Gas Range, 48", 8 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4'
Width	47 7/8"
Depth	29 1/8′

FEATURES & BENEFITS

Generous capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

COOKTOP POWER

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

EASY TO CLEAN

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Burner ratings

Maximum burner power	23500 BT
Power back centre	18500BT
Power back centre (2)	18500BT
Power back left	18500BT
Power back right	18500BT
Power front centre	18500BT
Power front centre (2)	18500BT
Power front left	23500BT
Power front right	23500BT
Total cooktop power	158000 BT

Capacity

Shelf positions	!
Total capacity (main oven)	5.3cu f
Total capacity second oven	2.4cu f
Usable capacity (main oven)	3.9cu f

Cleaning

Easy clean porcelain basepan	•
------------------------------	---

Controls

Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (natural gas)	6" to 9" W.C

Oven features

QUICK REFERENCE GUIDE > RGV3-488-N

Auto re-ignition system	•	Vent tr
Electronic oven control	•	
Full extension telescopic	•	Recom
Internal light	•	Combu
Titanium coated, illuminated	•	Non co
		Recom
Oven functions		
Bake	•	Safety
Broil	•	ADA co
Convection bake	•	
Slow cook	•	Full ex
Oven performance		Second
Oven performance	20 000 PTU	3/4 Ex
Main oven - Bake power	28,000 BTU	Electro
Main oven - Broil power	18,500 BTU	Interna
Secondary oven - Bake power	18,000 BTU	
Power requirements		Second
Amperage	15A	Bake
Rated current	15A	Conve
Supply frequency	60Hz	Numbe
		Proof
Product dimensions		Slow co
Depth	29 1/8"	
Depth (excluding handles)	29 1/8"	SKU
Height	35 3/4 - 36 3/4"	
Width	47 7/8"	
		The produ
Rangetop features		and mode specificati
Sealed range top	•	Paykel's C

•
s Ventilation
BGRV3-3048H
BGRV2-3048 / BGRV2-1248
HCB48-12_N (48" Professional
•
•
2
•
•
•
•
4
•
•
8199

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model

currently available. ? Fisher & Paykel Appliances Ltd 2020

QUICK REFERENCE GUIDE > RGV3-488-N Date: 04.04.2024 > 3

Other product downloads available at fisherpaykel.com



Guide d'utilisation FR



User Guide



Service & Warranty



Guide d'installation FR



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com