Wall Rangehood, 60cm, Telescopic

| Series 3 | Contemporary |
|----------|--------------|
| 001100 0 | contemporary |

White




The wall chimney rangehood has contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of 180m³/hr
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

| Height | 181-185mm |
|--------|-------------|
| Width | 598mm |
| Depth | 280 - 460mm |



FEATURES & BENEFITS

Easy installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Simple to use

Intuitive controls responds to the touch of your finger. Two halogen spotlights provide clear illumination over the entire cooking surface.

FISHER & PAYKEL

Easy cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless integration

With the white glass front panel handles and a brushed stainless steel finish, this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

| Accessories | |
|-------------------------|-----------------------------|
| 40mm Stainless handle | 792405 (included installed) |
| 40mm white glass handle | 792394 (included) |
| 70mm Stainless handle | 792399 (not included) |
| Aluminium filter | 792391 |

Accessories (sold separately)

| PD-RHK125E |
|---------------------|
| HS60 Part No.792399 |
| 791822 |
| 792390 |
| PD-RHK125T |
| PD-RHK125W |
| |

Fan ratings

| Maximum air movement | 180m³/hr |
|----------------------|----------|
| Maximum sound rating | 64dBA |

Installation and cleaning

Dishwasher safe filters

QUICK REFERENCE GUIDE > HS60LXW4

| Recirculation Optional - top and ba | | |
|-------------------------------------|-------------------------|--|
| | Optional - top and back | |
| Performance | | |
| Extraction type Surfa | ice | |
| Fan speeds | 2 | |
| Filter type Me | sh | |
| Number of filters | 2 | |
| Power requirements | | |
| Supply frequency 50 | Hz | |
| Supply voltage 220-240 | ov | |
| Product dimensions | | |
| Depth 280 - 460m | nm | |
| Height 181-185m | nm | |
| Width 598m | nm | |
| Product information | | |
| Control type Swit | ch | |
| Ventilation features | | |
| Light type Li | ED | |
| Warranty | | |
| Parts and labour 2 year | ars | |
| SKU 50 | 01 | |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

| 1 | |
|----------|--------------------|
| <u> </u> | Service & Warranty |

User Guide

↓

↓ Installation Guide



24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com