

DATA SHEET

790MM ACTIVESMART™ FRIDGE

Model no:

RF522BRZUX6, RF522BRPUX6

Product Dimensions	mm
Ⓐ Overall height* of fridge	1720
Ⓑ Overall width of fridge	790
Ⓒ Depth of fridge door and gasket	70
Ⓓ Depth of fridge door and chassis	695
Ⓔ Depth of fridge chassis (does not include fridge door)	625
Ⓕ Height of feet (adjustable)	24
Ⓖ Height from bottom of chassis to bottom of bottom door	16
Ⓗ Height from bottom of chassis to top of bottom door	626
Ⓜ Gap between doors	10
Ⓛ Height of top door	1060
Ⓧ Depth of door gasket	15
Ⓨ Depth of evaporator tray behind chassis	30
Ⓩ Depth of door (open at 90°) (measured from front of door)	745
Ⓨ Rotation of door (open)	138°




\* Includes mounted feet

Minimum Clearances	mm
Minimum height of cavity	1735
Minimum side clearance installed flush with chassis	20
Side clearance (hinge side) installed flush with door - full rotation	135
Rear clearance (including evaporator tray)	30

INDICATES PRODUCT DATUM .....  
 INDICATES CABINETRY CLEARANCES .....

DATE: 22.10.2015

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (3/32"). Please read the installation manual for detailed information on installing the product. [www.fisherpaykel.com](http://www.fisherpaykel.com)



0 100 200 400 millimetres