

# Warming Drawer, 30"

Series 9 | Professional

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook. Pair with a Professional-style oven for design cohesion.

- A companion product, designed to match with other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

## DIMENSIONS

Height	10 11/16"
Width	29 15/16"
Depth	22 3/8"

## FEATURES & BENEFITS

### Complementary design

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

### Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

### Easy to clean

<>

### Easy to use

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

### Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

### Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

## SPECIFICATIONS

### Accessories

Wire shelf	1
------------	---

## Capacity

Accessory rack maximum	42lb
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55lbs
Place settings	16
Usable depth	16 1/16"
Usable height	9 1/16"
Usable width	21 1/2"

## Cleaning

- Easy clean smooth-glass base

## Controls

- Audio feedback
- Automatic timers **30', 45', 1h, 2h, 4h, 6h**
- Delayed start
- Electronic capacitive touch
- On/Off indicator
- Pre-set heating functions
- Sabbath mode
- Soft close drawer
- Standby mode

## Functions

- Cups
- Dehydrate
- Number of functions **6**
- Plates
- Slow cook

Warm •

**Performance**

Heated glass base and fan •

Low temperature cooking •

Temperature levels **6**

Temperature range **95°F-185°F**

**Power requirements**

Amperage **10A**

Power outlet **3-prong grounding-type**

Supply frequency **60Hz**

Supply voltage **110V**

**Product dimensions**

Adjustable front door panel to •

Depth **22 3/8"**

Height **10 11/16"**

Width **29 15/16"**

**Safety**

Automatic turn off after 12 •

Full extension slides •

**Warranty**

Parts and labour **2 years**

SKU **82115**

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

**Other product downloads available at fisherpaykel.com**

- [↓](#) User Guide
- [↓](#) Guide D'Utilisation
- [↓](#) Installation Guide
- [↓](#) Guide D'Installation
- [↓](#) Data Sheet Warming Drawer
- [↓](#) Data Sheet Warming Drawer



**A PEACE OF MIND SALE**

**24 Hours 7 Days a Week Customer Support**

**T 1.888.936.7872 W www.fisherpaykel.com**