QUICK REFERENCE GUIDE > WB60SDEX2

Warming Drawer, 60cm

Series 9 | Contemporary

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Contemporary styling.

- A companion product, designed to match with other Contemporary style Fisher & Paykel products
- · Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	140mm
Width	596mm
Depth	567mm

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Capacity

Cappuccino cups

Espresso cups 42
Place settings 6
Usable depth 408mm
Usable height 98mm
Usable width 535mm

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback

Automatic pre-set

Automatic timers

30', 45', 1h, 2h, 4h, 6h

Delayed start

Electronic capacitive touch

On/Off indicator

Pre-set heating functions

Push-to-open drawer

Standby mode

Functions

Cups
Dehydrate
Number of functions
Plates
Slow cook
Warm

Performance

20

QUICK REFERENCE GUIDE > WB60SDEX2

Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
Temperature range	35°C-85°C

Power requirements

Amperage	10A
Power cord length	1800mm
Power outlet	3-prong grounding-type
Supply frequency	50Hz
Supply voltage	220V

Product dimensions

Adjustable front door panel to

Adjustable from door parier to	•
Depth	567mm
Height	140mm
Width	596mm

Safety

Automatic turn off after 12	•
Full extension slides	•

Warranty

Parts and labour	2 years
SKU	82107

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide Warming Drawer



User Guide



Installation Guide



Data Sheet Warming Drawer



Data Sheet Warming Drawer



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1300 650 590 Wwww.fisherpaykel.com