QUICK REFERENCE GUIDE > RGV2-304-L_N

Gas Range, 30", 4 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG




Professional style and performance, with powerful burners delivering high heat or the most gentle simmer.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 22,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Easy to clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design quality

This range has been carefully crafted in every detail from performance to durability using quality materials.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R30

Burner ratings

Maximum burner power	19000 BTU
Power back left	13000BTU
Power back right	13000BTU
Power front left	19000BTU
Power front right	15000BTU
Total cooktop power	60000 BTU

Capacity

Shelf positions	5
Shelf nositions (main oven)	5

QUICK REFERENCE GUIDE > RGV2-304-L_N
Date: 04.04.2024 > 2

Controls	3 wire	
Electric circuit		
Metal illuminated dials		
Gas Requirements		
Fitting and pipe	½ NPT, min. 5%" 🛭 flex line	
Supply Pressure (LPG)	11" to 14" W.C	
Oven features		
Auto re-ignition system	•	
Broil pan	•	
Electronic oven control	•	
Full extension telescopic	•	
Infrared Broiler	•	
Internal light	•	
Oven functions		
Bake	•	
Broil	•	
Convection bake	•	
Number of functions	3	
Oven performance		
Bake power	22,000 BTU	
Power requirements		
Amperage	15A	
Rated current	15A	
Supply frequency	60Hz	

Product dimensions	
Froduct difficultions	
Depth	29 1/8"
Depth (excluding handles)	29 1/8"
Height	35 3/4 - 36 3/4"
Width	29 7/8"
Rangetop features	
Sealed range top	•
Vent trim included	•
Recommended Back Guards	Ventilation
Combustible situation	BGRV2-3030H
Minimum CFM	600
Non combustible situation	BGRV2-3030 / BGRV2-1230
Non combustible situation Recommended hood	
Recommended hood	
Recommended hood Safety	BGRV2-3030 / BGRV2-1230 HCB30-6_N (Professional

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Guide d'installation FR



Installation Guide EN / Guide d'installation FR



Data Sheet Gas Range



Planning Guide Gas Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com