QUICK REFERENCE GUIDE > RDV2-305-N_N
Date: 04.04.2024 > 1

Dual Fuel Range, 30", 5 Burners

Series 9 | Professional

Stainless Steel | Natural gas




Make a statement in less space, with this powerful gas burner range and spacious convection oven.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Convection oven with 4 cu ft total capacity
- Non-tip full-extension shelves for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across, while the oven cavity is large enough to allow you to cook multiple dishes at once.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R30

Burner ratings

Maximum burner power	23500 BTU
Power back left	18500BTU
Power back right	18500BTU
Power centre	23500BTU
Power front left	18500BTU
Power front right	18500BTU
Total cooktop power	97500 BTU

Capacity

QUICK REFERENCE GUIDE > RDV2-305-N_N
Date: 04.04.2024 > 2

Shelf positions	5
Shelf positions (main oven)	5
Total capacity (main oven)	4L
Cleaning	
Pyrolytic self-clean	•
Controls	
Electric circuit	4 wire
Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (natural gas)	6" to 9" W.C
Oven features	
Auto re-ignition system	•
Broil pan	•
Concealed element	•
Electronic oven control	•
Full extension telescopic	•
Internal light	•
True convection	•
Oven functions	
Bake	•
Broil	•
Clean	•
Convection Broil	•
CONVECTION BION	

Number of functions	(
True convection	
Oven performance	
Bake power	3500W
Broil	4000 BTU
Main oven - True convection	2500W
Power requirements	
Amperage	304
Rated current	304
Supply frequency	60Н:
Product dimensions	
Depth	29 1/8
Height	35 3/4 - 36 3/4
Width	29 7/8
Rangetop features	
Sealed range top	
Vent trim included	
Recommended Back Guards \	/entilation
Combustible situation	BGRV2-3030H
Minimum CFM	600
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professiona

Full extension telescopic		
SKU	71374	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

QUICK REFERENCE GUIDE > RDV2-305-N_N
Date: 04.04.2024 > 3

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Guide d'installation FR



Installation Guide EN / Guide d'installation FR



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com