QUICK REFERENCE GUIDE > CPV3-486GD-L Date: 02.05.2024 > 1

Gas Rangetop, 48", Griddle, LPG

Series 9 | Professional

Stainless Steel | LPG



A powerful six burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Griddle with burners that deliver up to 19,000 BTU heat per burner, for seriously fast boiling
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from grilled cheese to quesadillas
- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16
Width	47 7/8'
Depth	28'

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

COOKING FLEXIBILITY

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

DESIGN QUALITY

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron trivets, and titanium coated dials.

SPECIFICATIONS

Sealed Dual Flow Burners™

Burner ratings			
Max burner power	Yes		
Power back centre	13000BTU		
Power back left Power back right Power front centre	13000BTU 13000BTU 15000BTU		
		Power front left	19000BTU
		Power front right Power griddle	15000BTU 15000BTU
Total cooktop power	103000BTU		
Burners			
Number of burners	6		
Cleaning			
Easy clean porcelain basepan	•		
Controls			
Metal illuminated dials	•		
Star K Certification	•		
Gas Requirements			
Fitting and pipe	½ NPT, min. %" 🛭 flex line		
Supply Pressure (LPG)	11" to 14" W.C		
Performance			
Auto re-ignition system	•		

QUICK REFERENCE GUIDE > CPV3-486GD-L Date: 02.05.2024 > 2

Sealed range top	
Simmer on all burners	140°F
Parameter and a second	
Power requirements	
Supply frequency	60H
Supply voltage	120\
Product dimensions	
Depth	28
Height	8 5/16
Width	47 7/8
Recommended Back Guards Ventilation	on

Combustible situation

Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N

BGCV2-3048H

6

Safety

ADA compliant

Warranty

Parts and labor Limited 2 years

Zones

Number of elements

SKU 82388 The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN



Planning Guide Professional Style Dial/Handle Accessories

