

Integrated Insert Rangehood, 60cm, with External Motor

Series 7 | Integrated

Stainless Steel and Glass



Seamlessly fits in cabinetry above your cooktop, with an external motor for near silent yet powerful extraction in the kitchen.

- External motor delivers near silent operation in the kitchen
- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful 1200m³/h maximum airflow
- Dimmable LED strip lighting illuminates the cooking surface beautifully

DIMENSIONS

Height	315mm
Width	530mm
Depth	280mm

FEATURES & BENEFITS

Near silent extraction

The powerful external motor is installed outside the home to deliver near silent extraction of cooking odours and steam from the kitchen.

Seamless integration

This rangehood can be built into your cabinetry for a seamless look. Its black glass control panel and stainless steel finish is designed to match the rest of Fisher & Paykel's kitchen appliance family.

EFFECTIVE EXTRACTION

This rangehood features three fan speeds plus boost function, providing powerful extraction to quickly remove odours and steam. As odours can linger in the kitchen well after cooking is finished, the timer keeps the rangehood running before automatically turning off.

Full surface lighting

Low energy, dimmable LED lights provide superb illumination over the entire cooking surface.

Easy to use

This Fisher & Paykel rangehood features a sleek and easy to use touch-control panel.

Easy cleaning

The glass and stainless steel finishes are easily wiped clean and the filters are simple to clean and dishwasher safe. An alert reminds you when to clean the filter and ensures you get the best performance out of your rangehood.

Considered efficiency

The four speeds with a range of different airflows means you can effectively remove cooking odours with reduced effect on your heating or air conditioning, ensuring less energy is used.

SPECIFICATIONS

Accessories

Aluminium filter	792942
External motor kit	50170 HB 1200E* (included)

Accessories (sold separately)

Extra ducting length	792961
Light bulb	requires service to replace

Fan ratings

Maximum air movement	1200m ³ /hr
Maximum pressured air	820m ³ /hr
Speed 1 sound rating	40dBA

Installation and cleaning

Dishwasher safe filters	2
Ducted	Top extraction
Stainless steel filter cover	•

Performance

Extraction type	Perimeter
Fan speeds	4
Number of filters	2

Power requirements

Supply frequency	50Hz
------------------	------

Supply voltage	240V
----------------	------

Product dimensions

Depth	280mm
-------	-------

Height	315mm
--------	-------

Width	530mm
-------	-------

Product information

Control type	Capacitive touch
--------------	------------------

Ventilation features

Dimmable lights	•
-----------------	---

Filter cleaning alert	•
-----------------------	---

Light type	LED strip
------------	-----------

Timer function	•
----------------	---

Warranty

Parts and labour	2 years
------------------	---------

SKU	50166
-----	-------

Other product downloads available at fisherpaykel.com

[Service & Warranty](#)[User Guide Integrated Insert Rangehood with External Blower](#)[Installation Guide Integrated Insert Rangehood with External Blower](#)[Installation Guide Rangehood External Blower](#)

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1300 650 590 W www.fisherpaykel.com

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020