QUICK REFERENCE GUIDE > RDV2-305-L\_N
Date: 04.04.2024 > 1

# Dual Fuel Range, 30", 5 Burners

Series 9 | Professional

Stainless Steel | LPG




Make a statement in less space, with this powerful gas burner range and spacious convection oven.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- Convection oven with 4 cu ft total capacity
- Non-tip full-extension shelves for safe removal of hot dishes

## **DIMENSIONS**

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"



#### **FEATURES & BENEFITS**

#### Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

## Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

#### Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

## Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

## Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across, while the oven cavity is large enough to allow you to cook multiple dishes at once.

## **SPECIFICATIONS**

## Accessories (sold separately)

Square handle option AH-R30

#### **Burner ratings**

Maximum burner power	19000 BTU
Power back left	11500BTU
Power back right	11500BTU
Power centre	19000BTU
Power front left	15000BTU
Power front right	15000BTU
Total cooktop power	72000 BTU

#### Capacity

QUICK REFERENCE GUIDE > RDV2-305-L\_N
Date: 04.04.2024 > 2

Shelf positions	5	
Shelf positions (main oven)	5	
Total capacity (main oven)	4L	
Cleaning		
Pyrolytic self-clean	•	
Controls		
Electric circuit	4 wire	
Metal illuminated dials	•	
Gas Requirements		
Fitting and pipe	½ NPT, min. 5%" 🛭 flex line	
Supply Pressure (LPG)	11" to 14" W.C	
Oven features		
Auto re-ignition system	•	
Broil pan	•	
Concealed element	•	
Electronic oven control	•	
Full extension telescopic	•	
Internal light	•	
True convection	•	
Oven functions		
Bake	•	
Broil	•	
Clean	•	
Convection Broil	•	
Convection bake	•	

Number of functions	6
True convection	•
Oven performance	
Bake power	3500W
Broil	4000 BTU
Main oven - True convection	2500W
Power requirements	
Amperage	304
Rated current	30 <i>A</i>
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8′
Height	35 3/4 - 36 3/4'
Width	29 7/8′
Rangetop features	
Sealed range top	•
Vent trim included	•
Recommended Back Guards	Ventilation
Combustible situation	BGRV2-3030H
Minimum CFM	600
	BGRV2-3030 / BGRV2-1230
Non combustible situation	

Full extension telescopic			•
SKU			71375

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

QUICK REFERENCE GUIDE > RDV2-305-L\_N
Date: 04.04.2024 > 3

# Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN / Guide d'installation FR



Data Sheet Dual Fuel Range



Planning Guide



## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com