QUICK REFERENCE GUIDE > HC90PCW1

Wall Rangehood, 90cm, Pyramid Chimney

Series 7 | Classic

White



Pairing well with the white Classic Freestanding Cooker, this wall chimney rangehood extracts steam and cooking odours effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- Dishwasher-safe filters that are easy to remove and clean
- Powerful 780m3/hr maximum airflow with edge-to-edge extraction
- · Energy-efficient LED lighting to illuminate your cooktop

DIMENSIONS

Height 636-975mm

Width 898mm

Depth 500mm

FEATURES & BENEFITS

Complementary Design

This wall chimney rangehood is designed to match the white Classic Freestanding Cooker in both colour and style, including stylish chrome touch buttons.

Cleaner Air

Odours can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 780m3/hr, this rangehood removes cooking odours effectively, as well as grease and steam while cooking.

Intuitive controls

Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

Simple to clean

Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

Design quality

Made from quality stainless steel with an excellent finish and robust product design, this rangehood is both visually appealing and durable.

Considered efficiency

The extraction rate ensures interior air and climate is not excessively removed to the outside, while LED lighting on the rangehood has been chosen for energy efficiency.

EASY INSTALLATION

This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Freestanding Cooker. It can be either externally ducted or internally recirculated, for simple installation

SPECIFICATIONS

Accessories	
Aluminium filter	792564

Accessories (sold separately)

Chimney extension	791774 (stainless steel),
Eave ducting kit	PD-RHK 150E
Light bulb	792556
Recirculation carbon filter	792481
Recirculation diverter	792560
Roof ducting kit	PD-RHK 150T
Side wall ducting kit	PD-RHK 150W

Fan ratings

Maximum air movement	780m³/hr
Speed 3 sound rating	65dBA

Installation and cleaning

3	Dishwasher safe filters
Vertical only	Ducted
Optional	Recirculation
•	Stainless steel filter cover
•	Two piece height adjustable

Performance

Extraction type Surface

QUICK REFERENCE GUIDE > HC90PCW1 Date: 02.05.2024 > 2

Fan speeds	3
Filter type	Mesh
Number of filters	3
Power requirements	
Lighting power	8W
Supply frequency	50Hz
Supply voltage	230V
Product dimensions	
Depth	500mm
Height	636-975mm
Width	898mm
Product information	
Control type	Classic style chrome touch
Ventilation features	
Light type	LED
Warranty	
Parts and labour	2 years
SKU	50154

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model

currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide



Installation Guide



24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com