QUICK REFERENCE GUIDE > CPV3-486GD-N

Gas Rangetop, 48", Griddle

Series 9 | Professional

Stainless Steel | Natural gas



A powerful six burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Griddle with burners that deliver up to 23,500 BTU heat per burner, for seriously fast boiling
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from grilled cheese to quesadillas
- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16
Width	47 7/8'
Depth	28'

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

PRECISE CONTROL

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

COOKING FLEXIBILITY

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

EASY TO CLEAN

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

INFORMATION AT A GLANCE

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

DESIGN QUALITY

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron trivets, and titanium coated dials.

SPECIFICATIONS

Burner ratings Max burner power Yes Power back centre 18500BTU Power back left 18500BTU Power back right 18500BTU Power front centre 18500BTU 23500BTU Power front left Power front right 18500BTU Power griddle 18000BTU Total cooktop power 134000BTU

Burners	
Number of burners	6

Easy clean porcelain basepan

Cleaning

Controls

Gas Requirements

Metal illuminated dials	•
Star K Certification	•

Fitting and pipe	½ NPT, min. ¾" 🛚 flex line
Supply Pressure (natural das)	6" to 9" W C

Performance		
Auto re-ignition system	•	
Sealed Dual Flow Burners™	6	
Sealed range top	•	
Simmer on all burners	140°F	

QUICK REFERENCE GUIDE > CPV3-486GD-N

Power requirements	
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	28"
Height	8 5/16"
Width	47 7/8"
Recommended Back Guards	Ventilation
Combustible situation	BGCV2-3048H
Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N
Safety	
ADA compliant	•
Warranty	
Parts and labor	Limited 2 years
Zones	
Number of elements	6

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher &

82387

SKU

Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide EN



Service & Warranty



Installation Guide EN



Planning Guide Professional Style Dial/Handle Accessories

