QUICK REFERENCE GUIDE > CG905DWNGFCX3

Gas on Steel Cooktop, 90cm, Flush Fit

Series 9 | Contemporary

Stainless Steel | Natural gas




Designed to fit flush into your kitchen benchtop, this large cooktop creates a seamless look and easy cleaning.

- A large cooking area with five burners, including a wok burner
- A flame-failure safety device; if a flame goes out, the gas turns off

DIMENSIONS

Height	76mm
Width	900mm
Depth	530mm



FEATURES & BENEFITS

Fits Flush

The gas burners are recessed into the work surface, leaving the trivets flush and providing an integrated kitchen bench with a seamless look.

Clever Cooking Results

The consistent flame and heat distribution of the dual flame wok burner, combined with highly responsive dials, offer precise heat adjustment that can perfect a slow simmer for sauces or an intense heat for searing steaks.

Complementary Design

The brushed stainless steel has been designed for durability but also provides a modern, stylish finish, matching the Fisher & Paykel family of kitchen appliances.

Safe And Sound

Intuitive dials glow red for on and white for off, showing from a distance which burners are lit. The flame failure safety device automatically turns off the gas if the flame is accidentally extinguished.

Easy Cleaning

The stainless steel component is easily accessible and quick to clean. Cast iron trivets provide a durable and stable cooking platform, with rubber feet to prevent them from scratching the cooktop.

Handy Accessories

This cooktop comes with a small pan support and wok stand to complement different cooking styles.

SPECIFICATIONS

Accessories Small pan support Wok stand •

Burner ratings

Auxiliary burner (natural gas)	4.2MJ/h
Rapid burner (natural gas)	10.5MJ/h
Semi-rapid burner (natural	9.1MJ/h
Wok burner (LPG)	6kW
Wok burner (natural gas)	21.5MJ/h
Wok burner power	21.5MJ/h

Burners

QUICK REFERENCE GUIDE > CG905DWNGFCX3

Cleaning Easy clean cooktop design Quick component removal Controls Burner indicator lights Dual wok control Laser etched graphics Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth S30mm Height 76mm Width 900mm Safety Flame failure system - Spill containment 2L	Number of burners	5
Controls Burner indicator lights Dual wok control Laser etched graphics Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage Product dimensions Depth Both LPG & SGOMM Height Flame failure system	Cleaning	
Controls Burner indicator lights • Dual wok control • Laser etched graphics • Metal illuminated dials • Turned stainless dials with • Performance Both LPG & NG models • Electronic ignition • Quick connect gas valves • Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system • **	Easy clean cooktop design	•
Burner indicator lights Dual wok control Laser etched graphics Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Quick component removal	•
Dual wok control Laser etched graphics Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Controls	
Laser etched graphics Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth Height 76mm Width 900mm Safety Flame failure system	Burner indicator lights	•
Metal illuminated dials Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Dual wok control	•
Turned stainless dials with Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth Height 76mm Width 900mm Safety Flame failure system	Laser etched graphics	•
Performance Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth Height 76mm Width 900mm Safety Flame failure system	Metal illuminated dials	•
Both LPG & NG models Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth Height 76mm Width 900mm Safety Flame failure system	Turned stainless dials with	•
Cast iron trivets Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Performance	
Electronic ignition Quick connect gas valves Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Both LPG & NG models	•
Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Cast iron trivets	•
Power requirements Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Electronic ignition	•
Supply voltage 230 - 240V Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Quick connect gas valves	•
Product dimensions Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Power requirements	
Depth 530mm Height 76mm Width 900mm Safety Flame failure system	Supply voltage	230 - 240V
Height 76mm Width 900mm Safety Flame failure system	Product dimensions	
Width 900mm Safety Flame failure system	Depth	530mm
Safety Flame failure system	Height	76mm
Flame failure system •	Width	900mm
	Safety	
Spill containment 2L	Flame failure system	•
	Spill containment	2L

Warranty	
Parts and labour	5 years
Zones	
Number of elements	5
SKU	81383
	01303

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

