

FISHER & PAYKEL

DATA SHEET

457mm Freezer + 762mm Fridge - Stainless Steel Integrated Columns

Model no:

RS4621FLJK1 + RS7621SRK1 shown

(Various models available to swap units to opposite sides, hinge doors both left, both right or at the outsides as shown here).

IMPORTANT!


For ease of installation, ensure cavity has consistent dimensions top to bottom and left to right.

Clearance Dimensions	mm
Ⓐ Overall height of cavity	2134
Ⓑ Overall width of cavity	1219
Ⓒ Minimum overall depth (shallow) of cavity when services are located outside of cavity*	635
Minimum overall depth (deep) of cavity when services are located at rear of cavity*	650
Ⓓ Width of supply area behind freezer	457
Ⓔ Width of supply area behind fridge	762
Ⓕ Height of supply area	229
Ⓖ Height at sides of supply area	127
Ⓜ Width from side of supply area	13
Ⓣ Combined width in side of supply areas	25
Ⓝ Depth of supply area	25
Minimum door cabinetry gap clearance	3

Optional Stainless Steel Panel Dimensions	mm
Ⓚ Height of door panel	2029
Ⓛ Width of freezer door panel	451
Ⓟ Width of fridge door panel	756
Ⓝ Depth of door panels	19
Ⓞ Height of toekick panel	100
Ⓟ Width of toekick panel	1215

*Connections may be located in an adjacent cabinet to either side of the fridge.

HANDLES: Handle Kits are sold separately. Shown with handle kit ADH3-RD21. Other style options available.



ISO VIEW OF 1219mm CAVITY
(457mm + 762mm)

DATE: 10.10.2018

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com