

Wall Rangehood, 90cm, Pyramid Chimney

Series 7 | Classic

Black



Pairing well with the black Classic Freestanding Cooker, this wall chimney rangehood extracts steam and cooking odours effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- Dishwasher-safe filters that are easy to remove and clean
- Powerful 780m³/hr maximum airflow with edge-to-edge extraction
- Energy-efficient LED lighting to illuminate your cooktop

DIMENSIONS

| | |
|--------|-----------|
| Height | 636-975mm |
| Width | 898mm |
| Depth | 500mm |

FEATURES & BENEFITS

COMPLEMENTARY DESIGN

This wall chimney rangehood is designed to match the black Classic Freestanding Cooker in both colour and style, including stylish chrome touch buttons.

CLEANER AIR

Odours can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 780m³/hr, this rangehood removes cooking odours effectively, as well as grease and steam while cooking.

INTUITIVE CONTROLS

Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

SIMPLE TO CLEAN

Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

DESIGN QUALITY

Made from quality stainless steel with an excellent finish and robust product design, this rangehood is both visually appealing and durable.

CONSIDERED EFFICIENCY

The extraction rate ensures interior air and climate is not excessively removed to the outside, while LED lighting on the rangehood has been chosen for energy efficiency.

EASY INSTALLATION

This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Freestanding Cooker. It can be either externally ducted or internally recirculated, for simple installation

SPECIFICATIONS

Accessories

| | |
|-----------------------------|-------------|
| Aluminium filter | 792564 |
| Chimney extension | 793223 |
| Eave ducting kit | PD-RHK 150E |
| Light bulb | 792556 |
| Recirculation carbon filter | 792481 |
| Recirculation diverter | 792560 |
| Roof ducting kit | PD-RHK 150T |
| Side wall ducting kit | PD-RHK 150W |

Fan ratings

| | |
|----------------------|-----------------------|
| Maximum air movement | 780m ³ /hr |
| Speed 3 sound rating | 65dBA |

Installation and cleaning

| | |
|------------------------------|---------------|
| Dishwasher safe filters | 3 |
| Ducted | Vertical only |
| Recirculation | Optional |
| Stainless steel filter cover | • |
| Two piece height adjustable | • |

Performance

| | |
|-----------------|---------|
| Extraction type | Surface |
| Fan speeds | 3 |
| Filter type | Mesh |

| | |
|-------------------|---|
| Number of filters | 3 |
|-------------------|---|

Power requirements

| | |
|------------------|------|
| Lighting power | 8W |
| Supply frequency | 50Hz |
| Supply voltage | 230V |

Product dimensions

| | |
|--------|-----------|
| Depth | 500mm |
| Height | 636-975mm |
| Width | 898mm |

Product information

| | |
|--------------|----------------------------|
| Control type | Classic style chrome touch |
|--------------|----------------------------|

Ventilation features

| | |
|------------|-----|
| Light type | LED |
|------------|-----|

Warranty

| | |
|------------------|---------|
| Parts and labour | 2 years |
|------------------|---------|

| | |
|-----|-------|
| SKU | 50153 |
|-----|-------|

Other product downloads available at fisherpaykel.com

[↓](#) Service & Warranty

[↓](#) Installation Guide

**A PEACE OF MIND SALE****24 Hours 7 Days a Week Customer Support****T 0800 372 273 W www.fisherpaykel.com**

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020