

# Warming Drawer, 24"

Series 9 | Minimal

Black



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Minimal design.

- A companion product, designed to match with other Minimal style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

## DIMENSIONS

|        |          |
|--------|----------|
| Height | 5 1/2"   |
| Width  | 23 7/16" |
| Depth  | 22 5/16" |

## FEATURES & BENEFITS

### Complementary design

Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.

### Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

### Easy to clean

<>

### Easy to use

Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

### Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

### Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

## SPECIFICATIONS

|                 |    |
|-----------------|----|
| Capacity        | 20 |
| Cappuccino cups |    |

|                          |          |
|--------------------------|----------|
| Espresso cups            | 42       |
| Maximum allowable weight | 55lbs    |
| Place settings           | 6        |
| Usable depth             | 16 1/16" |
| Usable height            | 3 7/8"   |
| Usable width             | 21 1/16" |

## Cleaning

- Easy clean smooth-glass base

## Controls

- Audio feedback
- Automatic timers **30', 45', 1h, 2h, 4h, 6h**
- Delayed start
- Electronic capacitive touch
- On/Off indicator
- Pre-set heating functions
- Push-to-open drawer
- Sabbath mode
- Soft close drawer
- Standby mode

## Functions

- Cups
- Dehydrate
- Number of functions **6**
- Plates
- Slow cook
- Warm

**Performance**

|                           |            |
|---------------------------|------------|
| Heated glass base and fan | •          |
| Low temperature cooking   | •          |
| Temperature levels        | 6          |
| Temperature range         | 95°F-185°F |

**Power requirements**

|                  |                        |
|------------------|------------------------|
| Amperage         | 10A                    |
| Power outlet     | 3-prong grounding-type |
| Supply frequency | 60Hz                   |
| Supply voltage   | 110V                   |

**Product dimensions**

|                                |          |
|--------------------------------|----------|
| Adjustable front door panel to | •        |
| Depth                          | 22 5/16" |
| Height                         | 5 1/2"   |
| Width                          | 23 7/16" |

**Safety**

|                             |   |
|-----------------------------|---|
| Automatic turn off after 12 | • |
| Full extension slides       | • |

**Warranty**

|                 |         |
|-----------------|---------|
| Parts and labor | 2 years |
|-----------------|---------|

|     |       |
|-----|-------|
| SKU | 82141 |
|-----|-------|

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

**Other product downloads available at fisherpaykel.com**

- [↓](#) Guide d'utilisation
- [↓](#) User Guide
- [↓](#) Service & Warranty
- [↓](#) Installation Guide
- [↓](#) Data Sheet Warming Drawer

**A PEACE OF MIND SALE**

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and