


FISHER & PAYKEL

DATA SHEET 24" Integrated Column Wine Cabinet

Model nos:
RS2484V2RK1 / RS2484V2LK1
with Stainless Steel Door Panel, Contemporary Square Handle and Stainless Steel Toekick Panel
NOTE: Left hand hinge model is a mirrored version of image shown.
(refer page 2 for metric measurements)



Product Dimensions	in
Ⓐ Overall height of product	84"
Ⓑ Overall width of product	23 3/4"
Ⓒ Depth of product front panels (excl. handles)	3/4"
Ⓓ Overall depth of product (excl. front door panels)	24"
Ⓔ Height from bottom datum to bottom of door	4"
Ⓕ Depth of toekick (excl. door front and toekick panels)	2 7/8" - 4"
Ⓖ Height of door panel	79 7/8"
Ⓜ Width of door panel	23 3/4"
Ⓣ Height from bottom datum to bottom of handle	32 1/8"
Ⓢ Height from bottom datum to top of handle	65 11/16"
Ⓚ Thickness of handles	5/8"
Ⓛ Distance from side of fridge to the center of handle	2 1/2"
Ⓝ Depth of handle (measured from front of door)	1 5/8"
Ⓤ Height of door glass	62 9/16"
Ⓞ Width of door glass	16 5/16"
Ⓟ Height from bottom of door to bottom of door glass	9 7/16"
Ⓠ Height from top of door to top of door glass	7 7/8"

Clearance Dimensions	in
Minimum cabinetry gap clearance from edge of door panel	1/8"
Overall height of cavity	84"
Overall width of cavity	24"
Minimum depth of cavity (including door panel) if: - power plug is located in an adjacent cabinet - power plug is located behind appliance	25" 25 9/16"
Minimum door clearance to adjacent wall (115° - full internal access)	14"
Minimum door clearance at 90° open, measured from front of door	26"
Minimum finished return inside cavity	4"

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 18.03.2020

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com

FISHER & PAYKEL


DATA SHEET 24" Integrated Column Wine Cabinet

Model nos:

**RS2484V2RK1 / RS2484V2LK1
with Stainless Steel Door Panel, Contemporary Square Handle
and Stainless Steel Toekick Panel**

NOTE: Left hand hinge model is a mirrored version of image shown.

(refer page 1 for imperial measurements)



Product Dimensions	mm
Ⓐ Overall height of product	2134
Ⓑ Overall width of product	603
Ⓒ Depth of product front panels (excl. handles)	19
Ⓓ Overall depth of product (excl. front door panels)	610
Ⓔ Height from bottom datum to bottom of door	102
Ⓕ Depth of toekick (excl. door front and toekick panels)	73 - 102
Ⓖ Height of door panel	2029
Ⓜ Width of door panel	603
Ⓣ Height from bottom datum to bottom of handle	816
Ⓤ Height from bottom datum to top of handle	1668
Ⓧ Thickness of handles	16
Ⓦ Distance from side of fridge to the centre of handle	64
Ⓨ Depth of handle (measured from front of door)	41
Ⓩ Height of door glass	1589
ⓐ Width of door glass	415
ⓑ Height from bottom of door to bottom of door glass	240
ⓓ Height from top of door to top of door glass	200

Clearance Dimensions	mm
Minimum cabinetry gap clearance from edge of door panel	3
Overall height of cavity	2134
Overall width of cavity	610
Minimum depth of cavity (including door panel) if:	
- power plug is located in an adjacent cabinet	635
- power plug is located behind appliance	650
Minimum door clearance to adjacent wall (115° - full internal access)	356
Minimum door clearance at 90° open, measured from front of door	660
Minimum finished return inside cavity	102

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: 18.03.2020

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com