QUICK REFERENCE GUIDE > HF60LX4

Wall Rangehood, 60cm, Fixed

Series 3 | Contemporary

Stainless Steel




This stainless steel rangehood has Contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With three fan speeds, select the perfect extraction rate for your cooking
- Efficient maximum air movement of 185m³/hr
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

| Height | 120mm |
|--------|-------|
| Width | 598mm |
| Depth | 450mm |



FEATURES & BENEFITS

Easy installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Simple Controls

Simply flick a switch to turn this rangehood on or off, or to change between three extraction speeds. A separate switch controls the bright halogen lights to provide illumination over your cooking surface.

Easy Cleaning

A filter, consisting of layers of aluminium mesh, effectively traps grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless Integration

The brushed stainless steel finish on this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (sold separately)

| PD-RHK125E |
|------------|
| 792507 |
| 792506 |
| PD-RHK125T |
| PD-RHK125W |
| |

Fan ratings

| Maximum motor performance | 350cm/hr |
|---------------------------|----------|
| Maximum pressured air | 185m³/hr |
| Maximum sound rating | 58dBA |

Installation and cleaning

| Dishwasher safe filters | 1 |
|-------------------------|-----------------------------|
| Ducted | Top extraction |
| Recirculation | Optional - front extraction |

Performance

| Extraction type | Surface |
|-----------------|---------|
| Fan speeds | 3 |

QUICK REFERENCE GUIDE > HF60LX4

| Filter type Number of filters | Mesh |
|--------------------------------|--------------|
| | |
| Supply frequency | 50Hz |
| Supply voltage | 220-240V |
| Product dimensions | |
| Depth | 450mm |
| Height | 120mm |
| Width | 598mm |
| Product information | |
| Control type | Push Button |
| Ventilation features | |
| Light type | Incandescent |
| Warranty | |
| Parts and labour | 2 years |
| SKU | 50010 |
| | |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions.

Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates
carbon emissions from a product's in-use energy. This is calculated either annually
or per cycle, using the product's market-specific energy label energy consumption
data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User & Installation Guide - Standard Rangehood

