QUICK REFERENCE GUIDE > RDV2-488-L_N

Date: 14.12.2023 > 1

Dual Fuel Range, 48", 8 Burners

Series 9 | Professional

Stainless Steel | LPG




A striking addition to your kitchen, with eight powerful gas burners and two ovens with a combined capacity of 6.9 cu ft.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two convection oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"	
Width	47 7/8"	
Depth	29 1/8"	



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R48

Burner ratings

Maximum burner power	19000 BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front centre (2)	15000BTU
Power front left	19000BTU
Power front right	19000BTU

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RDV2-488-L_N Date: 14.12.2023 > 2

Total cooktop power	120000 BTU	Supply frequency	60Hz
Capacity		Product dimensions	
Shelf positions	5	Depth	29 1/8"
Shelf positions (main oven)	5	Height	35 3/4 - 36 3/4"
Shelf positions (second oven)	5	Width	47 7/8"
Cleaning		Rangetop features	
Pyrolytic self-clean	•	Sealed range top	•
		Vent trim included	•
Controls		Safety	
Electric circuit	4 wire	Full extension telescopic	
Metal illuminated dials	• 		
Gas Requirements		Secondary oven features	
Fitting and pipe	NPT, min. %" 🛭 flex line	Broil	•
Supply Pressure (LPG)	11" to 14" W.C	Concealed element	•
		Electronic oven control	•
Oven features		Internal light	•
Auto re-ignition system	•		
Internal light	•	Secondary oven functions	
		Bake	•
Oven performance		Number of secondary oven	3
Bake power	4600	Proof	•
Broil	3600W		
Main oven - True convection	2500W	SKU	71367
Power requirements			
Rated current	50A	The product dimensions and specifications in this and model. Under our policy of continuous impro	

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

QUICK REFERENCE GUIDE > RDV2-488-L_N

Date: 14.12.2023 > 3

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Guide d'installation FR



Installation Guide



Guide D'Installation



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com