

FISHER & PAYKEL

DATA SHEET 300mm Induction Cooktop

Model no:
CI302DTB3

Product Dimensions	mm
Ⓐ Height of chassis (below top of bench including terminal block)	49
Ⓑ Overall width of cooktop	300
Ⓒ Overall depth of cooktop	530
Ⓓ Height from benchtop datum to top of cooktop glass	5
Ⓔ Width of chassis	257
Ⓕ Depth of chassis	478
Ⓖ Depth of front control panel	85
Ⓜ Depth of cooktop cooking area	442
Ⓛ Distance from side edges of cooktop to chassis	22
Ⓚ Distance from front edge of cooktop to chassis	14
Ⓛ Distance from back edge of cooktop to chassis	38


Minimum Clearances	mm
Minimum clearance from side edges of cutout to nearest combustible surface	30
Minimum clearance from rear edge of cutout to nearest combustible surface	30
Minimum clearance below top of benchtop to rear top of oven* installed below cooktop or cabinetry	65
Minimum clearance from glass surface to rangehood	650
Minimum clearance from benchtop to overhead cabinet not directly above the cooktop	450
Minimum ventilation gap between bottom of bench and top of cabinetry fronts	4

*NOTE: The oven installed below the cooktop MUST have a cooling fan. It is important that the induction cooktop receives adequate air supply. For ventilation requirements please refer to the installation manual.


INDICATES CUTOUT -----
INDICATES CABINETRY / PRODUCT DATUM -----
INDICATES CABINETRY CLEARANCES -----

DATE: 20.10.2016


IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



PLAN VIEW



FRONT VIEW




PROFILE VIEW



FISHER & PAYKEL

DATA SHEET 300mm Induction Cooktop

MULTIPLE ADJACENT COOKTOPS - EXAMPLE ONLY



CI302DTB3 INDUCTION COOKTOP
WITH JOINING STRIP AND
CG302DNGGB1 GAS ON GLASS COOKTOP

Model no:
CI302DTB3

Cutout Dimensions for CI302DTB3 only	mm
Overall width of cutout	265
Overall depth of cutout**	490

**Note cutout position is centred to the cooktop width but offset to the cooktop depth. Cutout front depth is 10mm from the front edge of the product.

Cutout Dimensions for CI302DTB3 with CG302DNGGB1	mm
Ⓐ Overall width of cutout	570
Ⓑ Overall depth of cutout	490
Ⓒ Width of CI302DTB3 Induction Cooktop section of cutout	265
Ⓓ Width of joining strip section of cutout	40
Ⓔ Width of CG302DNGGB1 Gas Cooktop section of cutout	265

Electrical Specifications for CI302DTB3 only

3700W @ 220-240V 1N - 16A***

***The CI302DTB3 comes supplied with cable. This must be wired into a suitably rated plug, permanent connector or power isolator.

IMPORTANT NOTE: For full installation and clearance details please refer to our installation manual.

DATE: 20.10.2016

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com