

90cm Series 7 Pyramid Chimney Wall Rangehood

Classic



Pairing well with the black Classic Freestanding Cooker, this wall chimney rangehood extracts steam and cooking odours effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- Dishwasher-safe filters that are easy to remove and clean
- Powerful 780m3/hr maximum airflow with edge-to-edge extraction
- Energy-efficient LED lighting to illuminate your cooktop

DIMENSIONS

Height 636-975 mm

Width 898 mm
Depth 500 mm

FEATURES & BENEFITS

Complementary Design
This wall chimney rangehood is designed to match the black Classic Freestanding Cooker in both colour and style, including stylish chrome touch buttons.

Cleaner Air
Odours can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 780m3/hr, this rangehood removes cooking odours effectively, as well as grease and steam while cooking.

Intuitive Controls
Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

Simple To Clean
Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

Design Quality
Made from quality stainless steel with an excellent finish and robust product design, this rangehood is both visually appealing and durable.

Considered Efficiency
The extraction rate ensures interior air and climate is not excessively removed to the outside, while LED lighting on the rangehood has been chosen for energy efficiency.

Easy Installation
This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Freestanding Cooker. It can be either externally ducted or internally recirculated, for simple installation

SPECIFICATIONS

Accessories (included)
Aluminium filter 792564

Accessories (sold separately)
Chimney extension 791774 (stainless steel), 793223 (black), 793224 (white), 793225 (red)
Eave ducting kit PD-RHK 150E
Light bulb 792556
Recirculation carbon filter 792481
Recirculation diverter 792560
Roof ducting kit PD-RHK 150T
Side wall ducting kit PD-RHK 150W

Fan ratings
Maximum air movement 780 m³/hr
Speed 3 sound rating 65 dBA

Installation and cleaning
Air outlet size 150 mm
Dishwasher safe filters 3
Ducted Vertical only
Recirculation Optional
Stainless steel filter cover •
Two piece height adjustable flue •

Performance
Extraction type Surface
Fan speeds 3

Filter type	Mesh
Number of filters	3

Power requirements

Lighting power	8 W
Supply frequency	50 Hz
Supply voltage	230 V

Product dimensions

Depth	500 mm
Height	636-975 mm
Width	898 mm

Ventilation features

Light type	LED
------------	-----

SKU	50153
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) Archicad
- [↓](#) Installation Guide (English)
- [↓](#) Revit
- [↓](#)

Rhino

- ↓ SketchUp
- ↓ User Guide (English)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' **In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 0800 372 273 W www.fisherpaykel.com