QUICK REFERENCE GUIDE > RDV2-488-N\_N
Date: 02.05.2024 > 1

# Dual Fuel Range, 48", 8 Burners

Series 9 | Professional

Stainless Steel | Natural gas




A striking addition to your kitchen, with eight high powered gas burners and two ovens with a combined capacity of 6.9 cu ft.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

## **DIMENSIONS**

Height	35 3/4 - 36 3/4"
Width	47 7/8"
Depth	29 1/8"



#### **FEATURES & BENEFITS**

#### **Cooktop Power**

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

## Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

## Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

## Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

## Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

#### **SPECIFICATIONS**

## Accessories (sold separately)

Square handle option AH-R48

#### Burner ratings

Maximum burner power	23500 BTU
Power back centre	18500BTU
Power back centre (2)	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front centre (2)	18500BTU
Power front left	23500BTU
Power front right	23500BTU

QUICK REFERENCE GUIDE > RDV2-488-N\_N
Date: 02.05.2024 > 2

Total cooktop power	158000 BTU
Capacity	
Shelf positions	5
Shelf positions (main oven)	5
Shelf positions (second oven)	5
Cleaning	
Pyrolytic self-clean	•
Controls	
Electric circuit	4 wire
Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %" 🛚 flex line
Supply Pressure (natural gas)	6" to 9" W.C
Oven features	
Auto re-ignition system	•
Internal light	•
Oven performance	
Bake power	4600
Broil	3600W
Main oven - True convection	2500W
Power requirements	
Rated current	50A

Supply frequency	60Hz
Product dimensions	
Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	47 7/8"
Rangetop features	
Sealed range top	•
Vent trim included	•
Safety	
Full extension telescopic	•
Secondary oven features	
Broil	•
Concealed element	•
Electronic oven control	•
Internal light	•
Secondary oven functions	
Bake	•
Number of secondary oven	3
Proof	•
	71366

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

## Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and

QUICK REFERENCE GUIDE > RDV2-488-N\_N
Date: 02.05.2024 > 3

# Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN / Guide d'installation FR



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com