QUICK REFERENCE GUIDE > RDV2-364GD-L_N
Date: 02.05.2024 > 1

Dual Fuel Range, 36", 4 Burners with Griddle

Series 9 | Professional

Stainless Steel | LPG




Get the best of gas and convection technology, with a powerful four burner gas cooktop and large capacity oven.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- Convection oven with 4.8 cu ft total capacity
- Non-tip full-extension shelves for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	35 7/8"
Depth	29 1/8"



FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R36

Burner ratings

Maximum burner power	19000 BTU
Power back left	13000BTU
Power back right	13000BTU
Power front left	19000BTU
Power front right	15000BTU
Power griddle	15000BTU
Total cooktop power	75000 BTU

Capacity

QUICK REFERENCE GUIDE > RDV2-364GD-L_N

Date: 02.05.2024 > 2

Shelf positions (main oven)	5	True convection
Cleaning		Oven performan
Pyrolytic self-clean	•	Bake power
Controls		Main oven - True
Electric circuit	4 wire	
Metal illuminated dials	- wiie	Power requireme
Metal Illuminated diais	·	Rated current
Gas Requirements		Supply frequency
Fitting and pipe	½ NPT, min. 5%" 🛭 flex line	Product dimensi
Supply Pressure (LPG)	11" to 14" W.C	Depth
		Height
Oven features		Width
Auto re-ignition system	•	Widen
Concealed element	•	Rangetop featur
Electronic oven control	•	Sealed range top
Full extension telescopic	•	Vent trim include
Internal light	•	7 6.112 6.111.1 11.10.14.40
Large broil pan	•	Safety
True convection	•	Full extension tel
Oven functions		
Bake	•	SKU
Broil	•	
Clean	•	
Convection Broil	•	The product dimensions and model. Under our p
Convection bake	•	specifications may char
Number of functions	6	Paykel's Customer Care currently available. Fish
Self-clean function	•	.,

•
4600
2500W
30A
60Hz
29 1/8"
35 3/4 - 36 3/4"
35 7/8"
•
•
•
7136

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Guide d'installation FR



Installation Guide EN / Guide d'installation FR



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com