

83cm Series 9 Minimal 4 Zone Induction Hob with Integrated Ventilation

Minimal



<p>A true two-in-one appliance, this hob combines the precision of induction cooking with powerful extraction in one seamless, stylish hob.</p>

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone
- With nine fan speeds plus boost, select the perfect extraction rate for your cooking

- Minimal style, sleek black glass finish to suit any kitchen design
- Works effectively in the background by recirculating vented air

DIMENSIONS

Height	217 mm
Width	830 mm
Depth	515 mm

FEATURES & BENEFITS

Seamless Integration

Offering true design freedom, this hob can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

Elegant Design

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these hobs seamlessly blend with other appliances for a cohesive, considered kitchen design.

Precise Control

Fisher & Paykel induction hobs offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

Effective Extraction

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background by recirculating vented air. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

Safety Of Induction

Induction hobs only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it – so they are safer for everyone.

Ease Of Use

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the hob surface.

Superior Efficiency

Less heat is wasted during induction cooking because only the cookware is heated, not the hob surface. This makes induction cooking more energy-efficient than electric or gas hobs.

SPECIFICATIONS

Accessories (sold separately)

Replacement recirculation filter	50183 FR-DD
----------------------------------	-------------

Cleaning

Dishwasher safe grease filter	•
Flat easy clean glass surface	•
Flush grille	•
Odour filter	3x Ceramic

Consumption

Energy rating	A+	Performance	Left rear	2100W
Controls		Gentle heat	Left rear zone (PowerBoost set)	3000W
Auto cut-off timer for each zone	•	Heat settings	Right front	2100W
Minute timer	•	Induction cooking technology	Right front zone (PowerBoost set)	3000W
Soft-touch electronic controls	•	Pause function	Right rear	2100W
Touch and slide controls	•	PowerBoost	Right rear zone (PowerBoost set)	3000W
		SmartZone	SmartZone	3700 W
Downdraft performance		Power requirements	Zones	
Air outlet size	333mm W x 33 mm H (Toekick outlet)	Electrical connection	Terminal block	Number of zones
Air speeds	9 + boost	Maximum power	7.4 kW	4
Brushless motor	•	Supply frequency	60 Hz	
Ducting Direction	Front (ducting included), Side & Rear (ducting optional)	Product dimensions		SKU
Maximum air flow (Boost)	660 m ³ /hr	Depth	515 mm	82234
Maximum air flow (Level 9)	623 m ³ /hr	Height	217 mm	
Maximum noise level (Boost)	70 dBA	Width	830 mm	
Maximum noise level (Level 9)	69 dBA	Safety		The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020
Minimum air flow	192 m ³ /hr	Keylock	•	Other product downloads available at fisherpaykel.com
Minimum noise level	38 dBA	Pan detection system	•	↓ DWG - Recirculated
Recirculation	•	Safety time out	•	↓ DXF
		Surface hot indicators	•	↓ Archicad
Ducting Accessories (optional)		Zone ratings		↓ Installation Guide (English)
Duct 1m Connector 218x55	82394 D1-C-218-55	Left front	2100W	↓ Planning Guide (English)
Elbow 90° 222x218x55	82395 E90-222218-55	Left front zone (PowerBoost set)	3000W	↓ Revit
				↓ Rhino
				↓ SketchUp

[↓](#) User Guide (English)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1800 625174 W www.fisherpaykel.com