QUICK REFERENCE GUIDE > RS6121SRK1

Integrated Column Refrigerator, 61cm

Series 11 | Integrated

Panel Ready | Right Hinge




Install it separately or pair with another Column for true design freedom - this model is right hinge with stainless steel interior.

- ActiveSmart[™] technology helps keep food fresher for longer by constantly maintaining the ideal temperature.
- Variable Temperature Zone lets you change a compartment to Fridge, Pantry or Chill for optimal storage
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory

DIMENSIONS

Height 2134mm
Width 603mm
Depth 610mm



FEATURES & BENEFITS

Mix & match

Integrated Column Refrigeration gives you the freedom to mix and match. Different sized Column Refrigerators and Freezers can be installed separately or paired. Finish them with our stainless steel door panels or customise to match your own kitchen cabinetry.

Perfect Fit

These models fit flush, with only 3mm gaps around them and no visible hinges or grilles. Our Integrated Column models can be

seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

CLEVER ENERGY

Our ActiveSmart™ Foodcare Refrigerator Freezers adapt to daily use by cooling and defrosting only when needed. This means your fridge uses the energy it needs without compromising on food care.

APPEALING ILLUMINATION

Bright LEDs light up each ceiling, shelves, bins and trays in both refrigerator and freezer, making it easy to find your food and creating a welcoming glow in your kitchen for those midnight snacks.

Design Quality

The premium design and quality finish include a stainless steel interior lining, full-extension metal shelf runners for easy access, and robust glass shelving.

EASY INSTALL

Integrated Column Refrigerators and Freezers have been developed to make their installation easy. The joiner kit is included when pairing refrigerators and freezers. All models come with front adjustable levelling feet and they've been designed to easily slide into place as separate units.

SPECIFICATIONS

Accessories (sold separately)

Door panel stainless steel	RD6121R10D
Handle kit Contemporary	AHS-RD21
Handle kit Contemporary	AHD5RDSF
Handle kit Contemporary	AHD5RDSFB
Handle kit Contemporary	AHD3-RD21
Joiner kit	AJ-RS21LR
Toe kick stainless steel	AKRS10710
Toe kick stainless steel	AKRS12210

QUICK REFERENCE GUIDE > RS6121SRK1 Date: 24.04.2024 > 2

Toe kick stainless steel 981mm AKRS19310 Frost free Fost	Toe kick stainless steel	AKRS13710	Adaptive defrost	•	
Toe kick stainless steel 1981mm AKRS19810 Toe kick stainless steel 610mm AKRS06110 Capacity Volume 351L Volume 351L Volume 751L Volume 7	Toe kick stainless steel	AKRS18310		•	
Toe kick stainless steel 610mm AKRS06110 Inverter controlled compressor 6.2 Capacity Noise emissions 42dBA Volume 351L Noise emissions class D Volume refrigerator 351L Sabbath mode . Consumption	Toe kick stainless steel 1981mm	AKRS19810	·	•	
Capacity Noise emissions 42d84 Volume 351L Noise emissions class D Volume refrigerator 351L Sabbath mode Consumption Energy rating 3 ticks Power requirements Energy usage 179kWh/year Rated current 10A Features Supply oftage 220 - 240V Adjustable door shelves 1 Product dimensions Covered door shelves 1 Product dimensions Sallon door shelves 1 Height 2134mm EED sin lighting 1 Width 603mm LED side lighting 1 Parts and labour 2 years Stackable bottle holders 4 Parts and labour 2 years Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions 5kU 26136 Minimum inside width of 610mm 5kU 26136 Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific produ	Toe kick stainless steel 610mm	AKRS06110		•	
Volume 351L Noise emissions class D Volume refrigerator 351L Sabbath mode . Variable temperature zones 2 Consumption Energy rating 3 ticks Power requirements Energy usage 179kWh/year Rated current 10A Supply frequency 50Hz Features Supply voltage 220 - 240V Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm • Depth 610mm Gallon door shelves 1 Height 2134mm LED bin lighting • Width 6603mm LED ceilling lighting • Width 6603mm LED side lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Minimum instee width of 610mm Minimum internal depth of 635mm Minimum internal depth of 635mm Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specific product and model. Under our policy of continuous improvement, these dimensions and specific product and model. Under our policy of continuous improvement, these dimensions and specific product and model. Un			Inverter controlled compressor	•	
Volume refrigerator 351L Sabbath mode . Variable temperature zones 2 Consumption Energy rating 3 ticks Power requirements Energy usage 179kWh/year Rated current 10A Supply frequency 50Hz Supply voltage 220 - 240V Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm • Depth 610mm Gallon door shelves 1 Height 2134mm LED bin lighting • Width 603mm LED ceiling lighting • Warranty Stackable bottle holders 4 Energy usage 179kWh/year Rated current 10A Supply voltage 220 - 240V Adjustable door shelves 1 Product dimensions Width 603mm Eab in lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Sealed system parts only 3 years Installation Dimensions Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and depolicy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specifications in this	Capacity		Noise emissions	42dBA	
Consumption Energy rating 3 ticks Energy usage 179kWh/year Rated current 10A Supply frequency 50Hz Supply voltage 220 - 240V Adjustable door shelves 1 Product dimensions Covered door shelves 1 Product dimensions Ballon door shelves 1 Height 2134mm LED bin lighting 1 Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Minimum internal depth of 635mm Minimum internal depth of 635mm Minimum internal height of 2134mm Minimum internal height of 2134mm Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and declarations in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and a model. Under our policy of continuous improvement, these dimensions and declarations in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and a model. Under our policy of continuous improvement, these dimensions and declarations in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and a model. Under our policy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model.	Volume	351L	Noise emissions class	D	
Consumption Energy rating 3 ticks Power requirements Energy usage 179kWh/year Rated current 10A Features Supply frequency 50Hz Adjustable door shelves 4 Supply voltage 220 - 240V Adjustable door shelves 1 Product dimensions Covered door shelves 1 Pepth 610mm Gallon door shelves 1 Height 2134mm LED bil lighting 1 Width 603mm LED ceiling lighting 1 Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Sealed system parts only 3 years Minimum inside width of 610mm SKU 26136 Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and and and model. Under our policy of continuous improvement, these dimensions and and and model. Under our policy of continuous improvement, these dimensions and and and model. Under our policy of continuous improvement, these dimensions and and and model. Under our policy of continuous improvement, these dimensions and and and model. Under our policy of continuou	Volume refrigerator	351L	Sabbath mode	•	
Energy rating 3 ticks Energy usage 179kWh/year Rated current 10A Supply frequency 50Hz Supply requency 220 - 240V Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm • Depth 610mm Gallon door shelves 1 Height 2134mm LED bin lighting • Width 603mm LED ceiling lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Minimum internal depth of 610mm Minimum internal depth of 635mm Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and			Variable temperature zones	2	
Energy usage 179kWh/year Rated current 10A Supply frequency 50Hz Features Supply voltage 220 - 240V Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm • Depth 610mm Gallon door shelves 1 Height 2134mm LED bin lighting • Width 603mm LED ceiling lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Minimum inside width of 610mm Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and and model. Under our policy of continuous improvement, these dimensions and and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications in this page apply to the specific product dimensions.	Consumption				
Features Supply frequency 50Hz Features Supply voltage 220 - 240V Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm • Depth 610mm Gallon door shelves 1 Height 2134mm LED bin lighting • Width 603mm LED ceiling lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Installation Dimensions Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Energy rating	3 ticks	Power requirements		
Features Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm 6 Depth 610mm 6allon door shelves 1 Height 2134mm LED bin lighting 1 Width 603mm LED celling lighting 1 Warranty Stackable bottle holders 4 Parts and labour Sealed system parts only 1 Sealed system parts	Energy usage	179kWh/year	Rated current	10A	
Adjustable door shelves 4 Covered door shelves 1 Product dimensions Door alarm			Supply frequency	50Hz	
Covered door shelves Door alarm Height Height 1 Height 2134mm 1 Height 1 Width 1 Height 1 Warranty 1 Height 1 Warranty 1 Height Height 1 Height 1 Height Height Height Height Height Height Height	Features		Supply voltage	220 - 240V	
Door alarm Door alarm I Depth Height 2134mm Height LED bin lighting Width Odd Height ED ceiling lighting Warranty Stackable bottle holders Have a selected system parts only Minimum inside width of Minimum internal depth of Minimum internal height of Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement.	Adjustable door shelves	4			
Gallon door shelves 1 Height 2134mm LED bin lighting • Width 603mm LED ceiling lighting • Warranty Stackable bottle holders 4 Parts and labour 2 years Sealed system parts only 3 years Installation Dimensions Minimum inside width of 610mm Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Covered door shelves	1	Product dimensions		
LED bin lighting . Width 603mm LED ceiling lighting . Warranty Stackable bottle holders 4 Parts and labour Sealed system parts only 3 years Installation Dimensions Minimum inside width of Minimum internal depth of Minimum internal depth of Minimum internal height of Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Door alarm	•	Depth	610mm	
LED ceiling lighting LED side lighting Stackable bottle holders 4 Parts and labour Sealed system parts only 3 years Installation Dimensions Minimum inside width of Minimum internal depth of Minimum internal height of Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and	Gallon door shelves	1	Height	2134mm	
LED side lighting Stackable bottle holders 4 Parts and labour Sealed system parts only Sealed system parts only 3 years Minimum inside width of Minimum internal depth of Minimum internal height of Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	LED bin lighting	•	Width	603mm	
Stackable bottle holders 4 Parts and labour Sealed system parts only 3 years Minimum inside width of Minimum internal depth of Minimum internal height of Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	LED ceiling lighting	•			
Stackable bottle holders A Parts and labour Sealed system parts only Sealed system parts only The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	LED side lighting	•	Warranty		
Minimum inside width of 610mm Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Stackable bottle holders	4	Parts and labour	2 years	
Minimum inside width of 610mm Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and			Sealed system parts only	3 years	
Minimum internal depth of 635mm SKU 26136 Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and model. Under our policy of continuous improvement, these dimensions and	Installation Dimensions		-	-	
Minimum internal height of 2134mm The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Minimum inside width of	610mm			
Performance The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and	Minimum internal depth of	635mm	SKU	26136	
Performance and model. Under our policy of continuous improvement, these dimensions and	Minimum internal height of	2134mm			
and model. Under our policy of continuous improvement, these dimensions and	Performance				
	ActiveSmart™ Foodcare	•			

Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

QUICK REFERENCE GUIDE > RS6121SRK1

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide Integrated Refrigerator Freezer EN



Installation Guide Integrated Column Refrigerator



Installation Guide Toe Kick



Specification Guide



Data Sheet Integrated Column Fridge



Data Sheet Integrated Column Fridge Dual Install (457mm + 610mm)



Data Sheet Integrated Column Fridge Dual Install (610mm



- Olomini,

Data Sheet Integrated Column Fridge Dual Install (610mm + 762mm)

<u>↓</u>

Data Sheet Integrated Column Fridge with Contemporary Square Handle Kit



Data Sheet Integrated Column Fridge with Contemporary Round Handle Kit



Planning Guide



Key Purchase Decisions Integrated Columns



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T +65 6741 0777 Wwww.fisherpaykel.com